

battery type: np4-6

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



| | | |
|-----|---------------------------------------------------------------------|-----------------------------|
| 1. | 公稱電壓 nominal voltage: | 6v |
| 2. | 尺寸 dimension | |
| | 長度 length: | 70.0±1 mm |
| | 寬度 width: | 47.0±1 mm |
| | 高度 height: | 102.0±1 mm |
| | 總高 total height: | 105.0±2 mm |
| 3. | 重量 weight(approx.) | 1.87pounds(0.85kg) |
| 4. | 公稱容量 nominal capacity: | |
| | 20 小時率 20hr rate of 0.2a to 5.25v | 4.0ah |
| | 3 小時率 3hr rate of 1.0a to 5.01v | 3.0ah |
| | 1 小時率 1hr rate of 2.4a to 4.80v | 2.4ah |
| 5. | 內部阻抗 internal resistance: | 19mΩ-22mΩ |
| 6. | 最大充電電流 max charged current: | 0.25ca (1.0a) |
| | 最大放電電流 max discharged current: | 60a(5 秒) |
| 7. | 操作溫度範圍 operation temperature range | |
| | 充電 charge | 5°F to 104°F(-15°C to 40°C) |
| | 放電 discharge | 5°F to 122°F(-15°C to 50°C) |
| 8. | 保存溫度範圍 storage temperature range | 5°F to 104°F(-15°C to 40°C) |
| 9. | 浮充 floating charge: | 6.825±0.15v |
| 10. | 壽命 expected life(25°C) | 3~5 years in float charging |
| 11. | 密閉構造 sealed construction | |
| | can be operated, charged or stored in any position without leakage. | |
| | can not be charged while the terminal is downward. | |
| 12. | 標準端子 standard terminal: | faston tab 187 |

| | | |
|-----|------------------------|-----|
| 13. | 電槽材質 housing material: | abs |
|-----|------------------------|-----|

| np4-6 constant wattage-typical run times(25°C, 77°F) | | | | | | | |
|------------------------------------------------------|------|------|------|------|-------|-------|-------|
| Time final voltage | 0.5m | 1.0m | 2.0m | 5.0m | 10.0m | 15.0m | 30.0m |
| 9.6v | 420w | 364w | 297w | 202w | 131w | 100w | 59.8w |
| 10.2v | 370w | 325w | 272w | 190w | 129w | 98w | 59.2w |
| 10.8v | 311w | 270w | 227w | 166w | 118w | 95w | 58.0w |

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)