

SPECIFICATION FOR APPROVAL

DOCUMENT: E4604TS001

STYLE : 105°C 600V
HOOK-UP WIRE

SIZE: 1346 4AWG × 1C
TS


RECOGNIZED: UL、CSA



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



WONDERFUL HI-TECHCO., LTD SPECIFICATION

STYLE	105°C 600V HOOK-UP WIRE	DOCUMENT NO : E4604TS001
SIZE	1346 4AWG ×1C	ESTABLISHED DATE: 1995/12/18
STANDARD : UL 758 & CSA C22.2 NO.210.2 APPLICATION:INTERNAL WIREING OF ELECTRONIC AND ELECTRICAL EQUIPMENT. CONSTRUCION:		
Conductor	Size	AWG 4AWG
	Material	---- TINNED COPPER
	Conductors Assembly	---- 437x31AWG
	O.D.	mm 6.5
Insulation	Average Thickness	mm 1.60
	Diameter	mm 9.7 ± 0.2
	Material	---- PVC
	Color	---- BLACK OR OTHER COLOR
Silver	Material	----
	Direction	----
	Thickness	μ m
	Al direction	----
Braid	Material	----
	Construction	mm
	Coverage	%
Jacket	Average Thickness	mm
	Diameter	mm
	Material	----
	Color	----
Marking	 AWM 1346 4AWG VW-1 105°C 600V E77981 WONDERFUL CSA AWM I A FT1 105°C 600V LL43774 (L.F)	
Drawing		

AK001/210X297/1.0

EDITION : 1.5

MAKER :

CONFIRM :

PAGE : 1

REVISED DATE : 2014.08.19

APPROVAL :



WONDERFUL HI-TECHCO., LTD

SPECIFICATION

Electrical & Physical Properties:			
Item		4AWG × 1C	
Rating Temp. Voltage		105°C 600V	
Conductor Resistance		0.88 OHM/KM/20°C MAX.	
Insulation Resistance		5 MEGA OHM-KM MIN.	
Dielectric Strength		AC 1.5 KV/MIN	
Spark Test		7.5 KV	
Insulation	Unaged	Tensile Strength	-----
		Elongation	-----
	Aged	Tensile Strength	-----
		Elongation	-----
Jacket	Unaged	Tensile Strength	1500 PSI MIN.(1.05 Kg / m m ²)
		Elongation	100% MIN.
	Aged	Tensile Strength	UNAGED MIN.70%(136°C x168HRS)
		Elongation	UNAGED MIN.65%(136°C x168HRS)
Deformation Test		MAX.50%(121°C x1HR)	
Heat Shock Test		121°C ×1Hr No Crack	
Cold Bend Test		-10°C ×4Hr No Crack	
Flame Test		VW-1 OK	

AK001/210X297/1.0

EDITION : 1.5

MAKER :

CONFIRM :

PAGE : 2

REVISED DATE : 2014.08.19

APPROVAL :

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)