


1813A Multi-Conductor - Two-Conductor, Low-Impedance Cable



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

For more Information
please call

1-800-Belden1



General Description:

24 AWG stranded (27x38) high-conductivity bare copper conductors, PVC insulation, bare copper spiral shield (90% coverage), PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
1	24	27x38	High Conductivity BC - Bare Copper

Total Number of Conductors:

2

Insulation

Insulation Material:

Insulation Material	Dia. (mm)
PVC - Polyvinyl Chloride	1.4986

Outer Shield

Outer Shield Material:

Type	Outer Shield Material	Coverage (%)
Spiral Serve	BC - Bare Copper	90.000

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter:

5.994 mm

Pair

Pair Color Code Chart:

Number	Color
1	Blue & Red

Mechanical Characteristics (Overall)

Operating Temperature Range: -30°C To +60°C

Bulk Cable Weight: 44.646 Kg/Km

Max. Recommended Pulling Tension: 44.482 N

Min. Bend Radius/Minor Axis: 63.500 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

EU Directive 2003/11/EC (BFR): Yes

CA Prop 65 (CJ for Wire & Cable): Yes

MII Order #39 (China RoHS): Yes

Plenum/Non-Plenum

Plenum (Y/N): No

1813A Multi-Conductor - Two-Conductor, Low-Impedance Cable

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/m)
0.718539

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
108.273

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)
200.141

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
74.8068

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
38.0596

Max. Operating Voltage - Non-UL:

Voltage
100 V RMS

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1813A B591000	1,000 FT	33.000 LB	BLACK, MATTE	C	2 #24 PVC SRV PVC
1813A B59328	328 FT	7.544 LB	BLACK, MATTE	C	2 #24 PVC SRV PVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 10-15-2012

© 2015 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.