



## Product: [3106A](#)

RS-485, 1 Pr, 22AWG, Str TC, PE Ins, with OS, 1C 22AWG Str, PVC Ins, OA TC Brd, PVC Jkt, CM, PLTC, Sun Res, Oil Resistant

 [Request Sample](#)

### Product Description

RS-485, 120 Ohm, 1 pair 22AWG (7x30) tinned copper Datalene® insulator, with Foil Shield, 1 Conductor 22AWG (7x30) Tinned Copper, PVC Insulated, Overall 65% Tinned Copper Braid, PVC jacket, CM, PLTC, SUN RES and oil-resistant

### Technical Specifications

#### Product Overview

|                        |                                                                                                |
|------------------------|------------------------------------------------------------------------------------------------|
| Suitable Applications: | harsh environment, IIoT, factory or process automation, video, audio, data communication, etc. |
|------------------------|------------------------------------------------------------------------------------------------|

#### Construction Details

##### Conductor

| Element      | No. of Elements | Size   | Stranding | Material           |
|--------------|-----------------|--------|-----------|--------------------|
| Pair(s)      | 1               | 22 AWG | 7x30      | TC - Tinned Copper |
| Conductor(s) | 1               | 22 AWG | 7x30      | TC - Tinned Copper |

##### Insulation

| Element      | Material                 | Nom. Thickness     | Nom. Insulation Diameter | Color Code                                | Notes |
|--------------|--------------------------|--------------------|--------------------------|-------------------------------------------|-------|
| Pair(s)      | PE - Polyethylene (Foam) | 0.033 in (0.84 mm) | 0.095 in (2.4 mm)        | White/Orange Stripe & Orange/White Stripe | HDPE  |
| Conductor(s) | PVC - Polyvinyl Chloride | 0.017 in (0.43 mm) | 0.062 in (1.6 mm)        | Blue/White Stripe                         |       |

##### Outer Shield

| Shield Type | Material                | Coverage | Drainwire Type   |
|-------------|-------------------------|----------|------------------|
| Tape        | Bi-Laminate (Alum+Poly) | 100%     | 22 AWG (7x30) TC |
| Braid       | Tinned Copper (TC)      | 65%      |                  |

##### Outer Jacket

| Material                 | Nom. Thickness    | Nom. Diameter      |
|--------------------------|-------------------|--------------------|
| PVC - Polyvinyl Chloride | 0.047 in (1.2 mm) | 0.310 in (7.87 mm) |

Overall Cable Diameter (Nominal): 0.310 in (7.87 mm)

#### Electrical Characteristics

##### Electricals

| Element      | Nom. Conductor DCR            | Nom. Capacitance Cond-to-Cond | Nom. Capacitance Cond-to-Other (Conds + Shield) | Nom. Characteristic Impedance | Nom. Inductance          | Nom. Velocity of Prop. | Max. Current                 |
|--------------|-------------------------------|-------------------------------|-------------------------------------------------|-------------------------------|--------------------------|------------------------|------------------------------|
| Pair(s)      | 18.2 Ohm/1000ft               | 11 pF/ft (36 pF/m)            | 20.9 pF/ft (68.6 pF/m)                          | 120 Ohm                       | 0.203 µH/ft (0.666 µH/m) | 78%                    | 6 Amps per Conductor at 30°C |
| Conductor(s) | 18.2 Ohm/1000ft (59.7 Ohm/km) |                               |                                                 |                               |                          |                        | 6 Amps per Conductor at 30°C |

Nom Outer Shield DCR: 4.544 Ohm/1000ft (14.91 Ohm/km)

##### High Frequency (Nominal/Typical)

| Element | Frequency [MHz] | Nom. Insertion Loss (Attenuation) |
|---------|-----------------|-----------------------------------|
| Pair(s) | 1               | 0.5 dB/100ft                      |

##### Voltage

[UL Voltage Rating](#)

300 V (CM, PLTC)

Mechanical Characteristics

Temperature

| UL Temperature | Operating      |
|----------------|----------------|
| 60°C           | -20°C to +60°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 3.6 in (91 mm)  | 3.6 in (91 mm)    |

|                    |                      |
|--------------------|----------------------|
| Max. Pull Tension: | 75.26 lbs (34.14 kg) |
| Bulk Cable Weight: | 48 lbs/1000ft        |

Standards and Compliance

|                                  |                                                                                                                           |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Environmental Suitability:       | Indoor, Outdoor, Sunlight Resistance, Oil Resistance                                                                      |
| Flammability / Reaction to Fire: | UL 1685 UL Loading, IEC 60332-1-2                                                                                         |
| CPR Compliance:                  | CPR Euroclass: Eca; CPR UKCA Class: Eca                                                                                   |
| NEC / UL Compliance:             | Article 725, Article 800, CM, PLTC                                                                                        |
| CEC / C(UL) Compliance:          | CM.                                                                                                                       |
| European Directive Compliance:   | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance:        | UKCA Mark                                                                                                                 |

Product Notes

|        |                                                                                                    |
|--------|----------------------------------------------------------------------------------------------------|
| Notes: | Oil Resistance: Passes Oil Res II Per UL1277, Table 10.17. For CPE jacketed version order YR46721. |
|--------|----------------------------------------------------------------------------------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.595 Revision Date: 02-20-2026 |
|----------------------|--------------------------------------------------|

Part Numbers

Variants

| Item #        | Color | Putup Type | Length   | UPC/EAN       | Footnote |
|---------------|-------|------------|----------|---------------|----------|
| 3106A.00152   | Black | Reel       | 152 m    | 8719605005892 |          |
| 3106A.00305   | Black | Reel       | 305 m    | 8719605005915 |          |
| 3106A 010500  | Black | Reel       | 500 ft   | 612825141662  | C        |
| 3106A 0101000 | Black | Reel       | 1,000 ft | 612825141655  | C        |
| 3106A.001525  | Black | Reel       | 1,525 m  | 8719605005908 |          |
| 3106A 0105000 | Black | Reel       | 5,000 ft | 612825141679  | C N      |

|           |                                                                                         |
|-----------|-----------------------------------------------------------------------------------------|
| Footnote: | C - CRATE REEL PUT-UP., N - FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN. |
|-----------|-----------------------------------------------------------------------------------------|

© 2026 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.