



**Product:** [1883A](#) 

Line Level Audio Cable, 1 Pr #24 Str TC, O/A Foil, PVC Jkt, CMR

## Product Description

Line Level Audio Cable, 1 Pair 24 AWG (7 x 32) Tinned Copper, PP insulation, Overall Beldfoil® Shield, PVC Jacket, CMR

## Technical Specifications

### Product Overview

Suitable Applications:	Line level audio; Low voltage analog signals
------------------------	--

### Construction Details

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	1	24 AWG	7x32	TC - Tinned Copper

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PP - Polypropylene	0.010 in (0.25 mm)	0.043 in (1.1 mm)	Black & Red

#### Outer Shield

Shield Type	Material	Coverage	Drainwire Type	Notes
Tape	Bi-Laminate (Alum+Poly)	100%	24 AWG (7x32) TC	Drain wire is inside foil shield.

#### Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PVC - Polyvinyl Chloride	0.020 in (0.51 mm)	0.129 in (3.28 mm)

Outer Jacket1 Table Notes:	Jacket and shield are bonded so both can be removed on automatic stripping equipment.
Overall Cable Diameter (Nominal):	0.129 in (3.28 mm)

### Electrical Characteristics

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Nom. Characteristic Impedance	Nom. Inductance	Nom. Velocity of Prop.	Max. Current
Pair(s)	28.8 Ohm/1000ft	31 pF/ft (100 pF/m)	58 pF/ft (190 pF/m)	52 Ohm	0.17 µH/ft (0.56 µH/m)	66%	3.8 Amps per conductor @ 30°C
Nom Outer Shield DCR@Cond DCR1-cnvc:			18.5 Ohm/1000ft (60.7 Ohm/km)				

#### Voltage

UL Voltage Rating
300 V (CMR)

### Mechanical Characteristics

#### Temperature

UL Temperature	Operating
60°C	-20°C to +60°C

#### Bend Radius

Stationary Min.	Installation Min.
1.2 in (30 mm)	1.2 in (30 mm)

Max. Pull Tension:	16.5 lbs (7.48 kg)
Bulk Cable Weight:	10 lbs/1000ft

## Standards and Compliance

Environmental Suitability:	Indoor - Riser, Indoor
Flammability / Reaction to Fire:	UL 1666 Riser, IEEE 1202 FT4, IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca
NEC / UL Compliance:	Article 800, CMR
CEC / C(UL) Compliance:	CMG
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
UK Regulation Compliance:	UKCA Mark
APAC Compliance:	China RoHS II (GB/T 26572-2011)

## Product Notes

Notes:	For cross-connect use with 1408R (et. al.) Snake Cables.
--------	--

## History

Update and Revision:	Revision Number: 0.461 Revision Date: 09-07-2025
----------------------	--

## Part Numbers

### Variants

Item #	Color	Putup Type	Length	UPC
1883A 0101000	Black	Reel	1,000 ft	612825126089
1883A 010U1000	Black	UnReel	1,000 ft	612825126072
1883A 010N1000	Black	Reel w/Small Barrel	1,000 ft	612825126065
1883A 010N2000	Black	Reel w/Small Barrel	2,000 ft	612825366997
1883A 0061000	Blue, Light	Reel	1,000 ft	612825125983
1883A 006U1000	Blue, Light	UnReel	1,000 ft	612825125976
1883A 006N1000	Blue, Light	Reel w/Small Barrel	1,000 ft	612825125969
1883A 006N2000	Blue, Light	Reel w/Small Barrel	2,000 ft	612825380184
1883A 0011000	Brown	Reel	1,000 ft	612825125907
1883A 001U1000	Brown	UnReel	1,000 ft	612825125891
1883A 001N1000	Brown	Reel w/Small Barrel	1,000 ft	612825125884
1883A 0081000	Gray	Reel	1,000 ft	612825126034
1883A 008U1000	Gray	UnReel	1,000 ft	612825126027
1883A 008N1000	Gray	Reel w/Small Barrel	1,000 ft	612825126010
1883A 008N2000	Gray	Reel w/Small Barrel	2,000 ft	612825366980
1883A N3U1000	Green, Mil	Reel	1,000 ft	612825125877
1883A N3UU1000	Green, Mil	UnReel	1,000 ft	612825125860
1883A N3UN1000	Green, Mil	Reel w/Small Barrel	1,000 ft	612825125846
1883A N3UN2000	Green, Mil	Reel w/Small Barrel	2,000 ft	612825125853
1883A 0021000	Red	Reel	1,000 ft	612825125938
1883A 002U1000	Red	UnReel	1,000 ft	612825125921
1883A 002N1000	Red	Reel w/Small Barrel	1,000 ft	612825125914
1883A 002N2000	Red	Reel w/Small Barrel	2,000 ft	612825366973
1883A 0071000	Violet	Reel	1,000 ft	612825126003
1883A 007U1000	Violet	UnReel	1,000 ft	612825125990
1883A 0091000	White	Reel	1,000 ft	612825126058
1883A 009U1000	White	UnReel	1,000 ft	612825126041
1883A 004N1000	Yellow	Reel w/Small Barrel	1,000 ft	612825125945
1883A 004N2000	Yellow	Reel w/Small Barrel	2,000 ft	612825125952

© 2025 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.