

EUM

勝特力材料 886-3-5753170
 勝特力電子(上海) 86-21-54151736
 勝特力電子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

PVC 絕緣 PVC 被覆 補償導線

特點

- 單股或多股芯線構成導體和雙層 PVC 材質絕緣
- 成本低廉，較精簡的構成方式
- 極佳的防水性及很好的耐化學藥品特性
- 具靈活和易彎曲的特性，施工安裝容易
- 顏色色碼：你可以選用 ANSI, IEC, JIS 等國際色碼。
- 如需增加耐磨強度：則以不銹鋼線或鍍錫銅線等材質編織外被覆。

導體

- (+) 銅
- (-) 銅鎳合金

絕緣

PVC (105°C)

被覆

PVC (105°C)

產品代號：W CAG 7/0.3*2

Grade of Wire	Thermocouple Extension Wire		
Part Numbers	W CAG 7/0.3*2		
Conductor	Positive	Copper	
	Negative	Constantan	
	Diameter	7/0.3mm * 1 Pair	
	Wire Type	Stranded	
	Standard Limits	±0.75%	
Insulation	PVC for 105°C		
	Insulation Wall	0.4mm	
	Color	Positive	Red
	Negative	White	
Jacket	PVC for 105°C		
	Insulation Wall	0.5mm	
	Color	Blue	
	Diameter	2.8 * 4.6 mm	
Weight (KG / 200m)		6.14KG	
Initial Calibration Tolerances ANSI			
Temperature Range		Standard Limits	Special Limits
-330°F (-200°C) to -165°F (-110°C)		±2%	
-165°F (-110°C) to +32°F (+0°C)		±4°F (2.2°C)	
+32°F (+0°C) to +545°F (+285°C)		±4°F (2.2°C)	±2°F (1.1°C)
+545°F (+285°C) to +2300°F (+1250°C)		±0.75%	±0.4%

