

勝特力電材超市-龍山店 886-3-5773766
 勝特力電材超市-光復店 886-3-5729570
 勝特力電子(上海) 86-21-34970699
 勝特力電子(深圳) 86-755-83298787
<http://www.100y.com.tw>

SPECIFICATION規格書

Specification 規格書

Name 品名 : Telephone Cable 【 Flat Cable 】

Spec 規格 : 28AWG x 8C

No.項次	Item(項目)	Value (規格值)	Tolerance
Conductor Structure 導體結構			
1.	Cond. Material (導體材質)	Bare Copper 退火軟銅線	-----
2.	Cond. Structure (導體結構)	0.12 mm / 7 (0.079mm ²)	±0.008 mm
3.	AWG/mm ² (美規公稱)	26AWG x 8C	-----
Insulation Structure 絕緣層結構			
4.	Ins. Material (絕緣材質)	Polypropylene (PP)	-----
5.	Ins. Thickness (絕緣厚度)	0.25mm (Average.)	mm
6.	Inner Wire Diameter (芯線外徑)	0.95 mm	±0.05 mm
7.	Color Code (芯線顏色)	灰.橘.黑.紅.綠.黃.藍.棕.	-----
Sheath Structure 外被層結構			
8.	Sheath Material (披覆材質)	PVC RoHS	-----
9.	Sheath Thickness (披覆厚度)	0.60 mm (Average.)	mm
10.	Overall Diameter (總完成外徑)	2.40 x 8.80 mm	±0.25 mm
Electronic Characteristic 電器特性			
11.	Voltage Testing (耐電壓測試)	1500 V / minute	-----
12.	Rated Voltage (額定耐壓)	30 V	V
13.	Rated Temperature (額定耐溫)	60 °C	°C
14.	Conductor Resistance(導體電阻)	152.0 Ω/KM (20°C) max	-----
15.	AC Volatge(耐壓試驗)	1500 V/Min (20°C)	-----

Structural Configuration (結構圖):

