



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

GREEN WIRE FOR OUR EARTH

WIRE/CABLE SPECIFICATION (線材規格書)

Standard		RSGE 8SQMM 200°C 300V		
Item (項目)		Unit (單位)	Specification (規格值)	Tolerance (容差)
General Specification (線種規格)		SQMM	8.0	
芯線結構	Conductor 導體	Material (材質)	-----	Tinned Copper
		Structure (結構)	No.×mm	50 / 0.45
		Stranded Diameter (絞線外徑)	mm	3.7 ±0.05
	Insulation 絕緣	Material (材質)	-----	Silicone Rubber
		Average Thickness (平均厚度)	mm	0.80 ±0.15
		Color (顏色)	-----	White
	Braid 編織	Material (材質)	-----	Fiberglass
		Wall Thickness (壁厚)	mm	0.2 ±0.02
	Color (顏色): White、Red、Black、Blue、Brown、Yellow、Green、Yellow/Green			
Overall Outer Diameter (最後完成外徑)		mm	5.70	±0.35
Electric Characters 電氣特性	Rated Temperature (額定溫度)		°C	200
	Rated Voltage (額定電壓)		V-AC	300
	Resistance of Insulation (水中常溫絕緣阻抗)		MΩ/km	50
	Withstand Voltage Spark (火花試驗)		KV/Sec	2
Certification		N/A		

Product Application (產品應用)

The wire can be used in various thermal places ranging from household appliances, lighting devices, industrial machines, to high-temperature furnace.

適用於各種家用電器, 照明燈具, 工業機器, 電熱製品, 原料溶爐等, 高溫場所之配線

Structural Configuration (結構圖):

