

DESCRIPTION

- Conductor : Silver coated copper clad steel
- Insulation : FEP Teflon
- Braid : Silver or Tinned coated copper
- Jacket : FEP Teflon
- Jacket Thickness : 0.08 ~ 0.15 mm.
- Temperature Range : -70°C ~ 200°C
- Voltage Rating : 30V

CHARACTERISTICS

- Continuous working temperature range : -70°C ~ 200°C
- Resistant to solvents, chemicals, gasoline and radiations.
- High Dielectric Strength permits extremely
- Minimal signal distortion
- Tough flexible resistant to crush, abrasion.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Document	Conductor		Insulation	Braid	Jacket	Capacitance (pF/ft)	Impedance (ohms)	ATT(dB/100m)	
	AWG	No./AWG Strands	Diameter (mm)	Coverage (%)	Diameter (mm)			Frequency(Hz)	2.4G
A3130CS001	30	7 x 30	0.8	93	1.27	29	50	310	520
A3132CS001	32	7 x 40	0.66	90	1.13	29	50	480	720
A3134SP001	34	7 x 42	0.53	97	0.98	29	50	530	780
A3136SP001	36	7 x 44	0.4	89	0.8	29	50	580	930

APPLICATIONS

Applications include mobile phone, PC and peripherals, home appliances, PDA, digital camera, GPS, network access device, video/audio equipment, security equipment, medical equipment, lighting equipment, remote control, wrist watch, car phone, hands-free voice-controlled device, broadcast equipment, identification card, shopping mail information etc.

SPECIFICATION FOR APPROVAL

DOCUMENT: A3132SP003

STYLE : COAXIAL CABLE
105°C 30V


SIZE: 32AWG×1C
BRAID : SP

RECOGNIZED: UL 1979

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



SPECIFICATION

STYLE	105°C 30V UL 1979	DOCUMENT NO : A3132SP003	
SIZE	32AWG	ESTABLISHED DATE: 2009/01/17	
STANDARD :			
Conductor	Size	AWG	32
	Material	----	Silver Cover Copper
	Conductors No.	----	7
	Conductors Size	mm	0.085
	O.D.	mm	0.22
Insulation	Average Thickness	mm	0.20
	Diameter	mm	0.70 ± 0.02
	Material	----	FEP
	Color	----	Clear
Braid	Material	----	Silver Cover Copper
	Construction	mm	16 / 4 / 0.050
	Coverage	%	90.4
Jacket	Average Thickness	mm	0.12
	Diameter	mm	1.13 ± 0.05
	Material	----	FEP
	Color	----	According to custom
Marking	Non		
Drawing	 <div style="border: 2px solid red; padding: 5px; margin-top: 10px;"> <p>勝特力材料 886-3-5753170 勝特力电子(上海) 86-21-34970699 勝特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw</p> </div>		

AK001/210X297/1.0

PAGE : 1

EDITION : 1.2

MAKER : *H. C. KUO*

CONFIRM : *C. Y. Chen*

APPROVAL : *W. J. Wang*



SPECIFICATION

Electrical & Physical Properties					
Item	32AWG				
Rating Temp Voltage	105°C 30V				
Conductor Resistance	850 OHM/KM/20°C MAX.				
Insulation Resistance	1000 MEGA OHM-KM MIN.				
Dielectric Strength	AC 500 V/Minute				
Spark Test	2.5 KV				
Insulation	Unaged	Tensile Strength	2500 PSI MIN.(1.76 Kg / m m ²)		
		Elongation	200% MIN.		
	Aged	Tensile Strength	UNAGED MIN. 75%(168HRS×232°C)		
		Elongation	UNAGED MIN. 75%(168HRS×232°C)		
Jacket	Unaged	Tensile Strength	2500 PSI MIN.(1.76 Kg / m m ²)		
		Elongation	200% MIN.		
	Aged	Tensile Strength	UNAGED MIN.75%(168HRS×232°C)		
		Elongation	UNAGED MIN.75%(168HRS×232°C)		
Nom. Impedance	50 ± 3 Ohms				
Nom. Capacitance	96 ± 3 pF/m				
Nom. Vel. of Prop.	69%				
VSWR Test (0 – 6 GHZ)	Max 1.3				
Flame Test	VW-1 OK				
Attenuation (dB/1m)	2.0GHZ	2.4GHZ	2.5GHZ	5.0GHZ	6.0 GHZ
	2.80	3.10	3.15	4.85	5.20