

DESCRIPTION

- Conductor : Silver coated copper clad steel
- Insulation : FEP Teflon
- Braid : Silver or Tinned coated copper
- Jacket : FEP Teflon
- Jacket Thickness : 0.08 ~ 0.15 mm.
- Temperature Range : -70°C ~ 200°C
- Voltage Rating : 30V

CHARACTERISTICS

- Continuous working temperature range : -70°C ~ 200°C
- Resistant to solvents, chemicals, gasoline and radiations.
- High Dielectric Strength permits extremely
- Minimal signal distortion
- Tough flexible resistant to crush, abrasion.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Document	Conductor		Insulation	Braid	Jacket	Capacitance (pF/ft)	Impedance (ohms)	ATT(dB/100m)	
	AWG	No./AWG Strands	Diameter (mm)	Coverage (%)	Diameter (mm)			Frequency(Hz)	2.4G
A3130CS001	30	7 x 30	0.8	93	1.27	29	50	310	520
A3132CS001	32	7 x 40	0.66	90	1.13	29	50	480	720
A3134SP001	34	7 x 42	0.53	97	0.98	29	50	530	780
A3136SP001	36	7 x 44	0.4	89	0.8	29	50	580	930

APPLICATIONS

Applications include mobile phone, PC and peripherals, home appliances, PDA, digital camera, GPS, network access device, video/audio equipment, security equipment, medical equipment, lighting equipment, remote control, wrist watch, car phone, hands-free voice-controlled device, broadcast equipment, identification card, shopping mail information etc.

SPECIFICATION FOR APPROVAL

DOCUMENT: A3236SC002

STYLE : 36AWG Coaxial Cable

SIZE: 7/0.05mm SP

RECOGNIZED: UL 1979

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)




SPECIFICATION

Electrical & Physical Properties					
Item		36AWG Coaxial Cable			
Rating Temp Voltage		105°C 30V			
Conductor Resistance		1394 OHM/KM/20°C MAX.			
Insulation Resistance		3000 MEGA OHM-KM MIN.			
Dielectric Strength		AC 1000V/Minute			
Spark Test		2 KV			
Insulation	Unaged	Tensile Strength	2500 PSI MIN.(1.76 Kg / m m ²)		
		Elongation	200% MIN.		
	Aged	Tensile Strength	UNAGED MIN 75%(168HRS×232°C)		
		Elongation	UNAGED MIN 75%(168HRS×232°C)		
Jacket	Unaged	Tensile Strength	2500 PSI MIN.(1.76 Kg / m m ²)		
		Elongation	200% MIN.		
	Aged	Tensile Strength	UNAGED MIN.85%(96HRS×260°C)		
		Elongation	UNAGED MIN.85%(96HRS×260°C)		
Nom. Impedance		75 ±3 Ohms			
Nom. Capacitance		65 pF/m			
Nom. Vel. of Prop.		69.5%			
VSWR (0 – 6 GHZ)		UNDER 1.3			
Attenuation (dB/1m)	1GHz	1.8GHz	2.4GHz	5.2GHz	6GHz
	3.14	3.82	4.34	7.44	8.04



SPECIFICATION

STYLE	105°C 30V UL1979	DOCUMENT NO : A3236SC002	
SIZE	36AWG Coaxial Cable	ESTABLISHED DATE: 2012/02/08	
STANDARD : MIL-C-17			
Conductor	Size	AWG	36
	Material	----	Silver-Coated Copper
	Conductors No.	----	7
	Conductors Size	mm	0.05
	O.D.	mm	0.12±0.005
Insulation	Average Thickness	mm	0.27
	Diameter	mm	0.69 ±0.03
	Material	----	FEP
	Color	----	Clear
Braid	Material	----	Silver-Coated Copper
	Construction	mm	16 / 5 / 0.05
	Coverage	%	98
Jacket	Average Thickness	mm	0.245
	Diameter	mm	1.37 ±0.05
	Material	----	FEP
	Color	----	Black
Marking	Non		
Drawing	 <div style="border: 2px solid red; padding: 5px; margin-top: 10px;"> <p>勝特力材料 886-3-5753170 勝特力电子(上海) 86-21-34970699 勝特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw</p> </div>		

AK001/210X297/1.0

PAGE : 1

EDITION : 1.0

MAKER : *H. C. KUO*

CONFIRM : *S. N. Wong*

APPROVAL : *W. J. Wang*