

300V PVC-PVC 輕便電纜(VCTF)



- 規格：參考 CNS 3199
- 用途：低壓電器及室內用
- 額定：300V 以下
- 構造：導體- 圓形軟銅絞線
絕緣- PVC
被覆- PVC
- 識別：1C:黑、2C:白、3C:紅、4C:綠
5C 以上為黑色絕緣印白色線號 NO.1-NO.XX(指定芯數)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

標稱截面積	導體		絕緣體厚度	被覆體厚度	完成外徑 (約)	最大導體電阻 (20℃)	交流耐電壓 (A.C.)		最小絕緣電阻		火花試驗
	組成	外徑 (約)					(水中)	(空中)	(20℃)	(60℃)	
mm ² xC	No./mm	mm	mm	mm	mm	Ω/km	kV/分		MΩ-km	kV/Sec	
0.5 x 2	20/0.18	0.9	0.6	1.0	6.1	37.8	1/1	3/1	5	0.01	5/0.15
0.5 x 3					6.5						
0.5 x 4					7.0						
0.5 x 5					7.7						
0.5 x 6					8.3						
0.5 x 7					8.3						
0.5 x 8					9.0						
0.5 x 10					10.4						
0.5 x 12					10.8						
0.5 x 16					11.9						
0.5 x 20					13.2						
0.5 x 24					14.6						
0.5 x 30					15.5						
0.5 x 36					16.7						
0.75 x 2	30/0.18	1.1	0.6	1.0	6.5	25.1	1/1	3/1	5	0.01	5/0.15
0.75 x 3					6.9						
0.75 x 4					7.5						
0.75 x 5					8.3						
0.75 x 6					8.9						
0.75 x 7					8.9						
0.75 x 8					9.7						
0.75 x 10					11.2						
0.75 x 12					11.6						
0.75 x 16					12.9						
0.75 x 20					14.3						
0.75 x 24					15.8						
0.75 x 30					16.8						
0.75 x 36					18.2						
1.25 x 2	50/0.18	1.5	0.6	1.0	7.3	15.1	1/1	3/1	5	0.01	5/0.15
1.25 x 3					7.8						
1.25 x 4					8.5						
1.25 x 5					9.3						
1.25 x 6					10.1						
1.25 x 7					10.1						
1.25 x 8					11.0						
1.25 x 10					12.8						
1.25 x 12					13.3						
1.25 x 16					14.7						
1.25 x 20					16.4						
1.25 x 24					18.3						
1.25 x 30					19.5						
1.25 x 36					21.0						
2 x 2	37/0.26	1.8	0.6	1.0	7.9	9.79	1/1	3/1	5	0.01	5/0.15
2 x 3					8.4						
2 x 4					9.2						
2 x 5					10.1						
2 x 6					11.0						
2 x 7					11.0						
2 x 8					12.0						
2 x 10					14.0						
2 x 12					14.5						
2 x 16					16.1						
2 x 20					18.1						
2 x 24					20.1						
2 x 30					21.4						
2 x 36					23.1						