

WIMA MKS 4



Metallized Polyester (PET) Capacitors PCM 7.5 mm to 37.5 mm

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

Special Features

- High volume/capacitance ratio
- Self-healing
- According to RoHS 2002/95/EC

Typical Applications

For general DC-applications e.g.

- By-pass
- Blocking
- Coupling and decoupling
- Timing

Construction


Dielectric:

Polyethylene-terephthalate (PET) film

Capacitor electrodes:

Vacuum-deposited

Internal construction:



Encapsulation:

Solvent-resistant, flame-retardant plastic case with epoxy resin seal, UL 94 V-0

Terminations:

Tinned wire.

Marking:

Colour: Red. Marking: Black.
 Epoxy resin seal: Red

Electrical Data

Capacitance range:

1000 pF to 220 μF (E12-values on request)

Rated voltages:

50 VDC, 63 VDC, 100 VDC, 250 VDC, 400 VDC, 630 VDC, 1000 VDC, 1500 VDC, 2000 VDC

Capacitance tolerances:

±20%, ±10% ±5%

Operating temperature range:

-55° C to +100° C

Climatic test category:

55/100/56 in accordance with IEC

Insulation resistance at +20° C:

U _r	U _{test}	C ≤ 0.33 μF	0.33 μF < C ≤ 220 μF
50 VDC	10V	≥ 5 x 10 ³ MΩ (mean value: 3 x 10 ⁴ MΩ)	≥ 1500 sec (MΩ x μF) (mean value: 4500 sec)
63 VDC	50V	≥ 1 x 10 ⁴ MΩ (mean value: 5 x 10 ⁴ MΩ)	≥ 3000 sec (MΩ x μF) (mean value: 6000 sec)
100 VDC	100V	≥ 1.5 x 10 ⁴ MΩ (mean value: 5 x 10 ⁴ MΩ)	≥ 5000 sec (MΩ x μF) (mean value: 15000 sec)
≥ 250 VDC	100V	≥ 3 x 10 ⁴ MΩ (mean value: 1 x 10 ⁵ MΩ)	≥ 10000 sec (MΩ x μF) (mean value: 40000 sec)

Test voltage: 1.6 U_r, 2 sec.

Test specifications:

In accordance with IEC 60384-2 and EN 130400

Voltage derating:

A voltage derating factor of 1.25 % per K must be applied from +85° C for DC voltages and from +75° C for AC voltages.

Reliability:

Operational life > 300 000 hours
 Failure rate < 2 fit (0.5 x U_r and 40° C)

Measuring time: 1 min.

Dissipation factors at +20° C: tan δ

at f	C ≤ 0.1 μF	0.1 μF < C ≤ 1.0 μF	C > 1.0 μF
1 kHz	≤ 8 x 10 ⁻³	≤ 8 x 10 ⁻³	≤ 10 x 10 ⁻³
10 kHz	≤ 15 x 10 ⁻³	≤ 15 x 10 ⁻³	-
100 kHz	≤ 30 x 10 ⁻³	-	-

Maximum pulse rise time:

Capacitance pF/μF	Pulse rise time V/μsec max. operation/test								
	50VDC	63VDC	100VDC	250VDC	400VDC	630VDC	1000VDC	1500VDC	2000VDC
1000 ... 6800	-	-	-	-	-	-	70/700	90/900	100/1000
0.01 ... 0.022	-	30/300	30/300	35/350	38/380	40/400	50/500	50/500	60/600
0.033 ... 0.068	-	15/150	15/150	20/200	25/250	32/320	26/260	35/350	40/400
0.1 ... 0.22	10/100	10/100	12/120	15/150	15/150	17/170	20/200	35/350	40/400
0.33 ... 0.68	9/90	9/90	9/90	10/100	10/100	13/130	20/200	20/200	38/380
1.0 ... 2.2	6/60	6/60	5/50	6/60	9/90	13/130	14/140	15/150	-
3.3 ... 6.8	2.5/25	3/30	3/30	6/60	6/60	9/90	12/120	-	-
10 ... 220	2.5/25	2.5/25	2.5/25	3/30	6/60	-	-	-	-

for pulses equal to the rated voltage

Mechanical Tests

Pull test on leads:

d ≤ 0.8 φ: 10 N in direction of leads
 d > 0.8 φ: 20 N in direction of leads
 according to IEC 60068-2-21

Vibration:

6 hours at 10...2000 Hz and 0.75 mm displacement amplitude or 10 g in accordance with IEC 60068-2-6

Low air density:

1kPa = 10 mbar in accordance with IEC 60068-2-13

Bump test: 4000 bumps at 390 m/sec² in accordance with IEC 60068-2-29

Packing

Available taped and reeled up to and including case size 15 x 26 x 31.5 / PCM 27.5 mm.

Detailed taping information and graphs at the end of the catalogue.

For further details and graphs please refer to Technical Information.

Continuation

勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-34970699

勝特力电子(深圳) 86-755-83298787

Http://www.100y.com.tw

General Data


Capacitance	50 VDC/30 VAC*					63 VDC/40 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
0.01 μ F						2.5	7	10	7.5	MKS4C021002A00
0.015 "						4	9	13	10	MKS4C021003C00
0.022 "						2.5	7	10	7.5	MKS4C021502A00
0.033 "						4	9	13	10	MKS4C021503C00
0.047 "						2.5	7	10	7.5	MKS4C022202A00
0.068 "						4	9	13	10	MKS4C022203C00
						2.5	7	10	7.5	MKS4C023302A00
						4	9	13	10	MKS4C023303C00
						2.5	7	10	7.5	MKS4C024702A00
						4	9	13	10	MKS4C024703C00
						2.5	7	10	7.5	MKS4C026802A00
						4	9	13	10	MKS4C026803C00
0.1 μ F	2.5	7	10	7.5	MKS4B031002A00	2.5	7	10	7.5	MKS4C031002A00
0.15 "	2.5	7	10	7.5	MKS4B031502A00	4	9	13	10	MKS4C031003C00
0.22 "	2.5	7	10	7.5	MKS4B032202A00	2.5	7	10	7.5	MKS4C031502A00
0.33 "	2.5	7	10	7.5	MKS4B033302A00	4	9	13	10	MKS4C031503C00
0.47 "	3	8.5	10	7.5	MKS4B034702B00	3	8.5	10	7.5	MKS4C032202B00
0.68 "	4	9	10	7.5	MKS4B036802C00	4	9	13	10	MKS4C032203C00
						4	9	10	7.5	MKS4C033302C00
						4	9	13	10	MKS4C033303C00
						4	9	10	7.5	MKS4C034702C00
						4	9	13	10	MKS4C034703C00
						5	10.5	10.3	7.5	MKS4C036802E00
						4	9	13	10	MKS4C036803C00
1.0 μ F	4	9	10	7.5	MKS4B041002C00	5	10.5	10.3	7.5	MKS4C041002E00
1.5 "	5	10.5	10.3	7.5	MKS4B041502E00	4	9	13	10	MKS4C041003C00
2.2 "	5.7	12.5	10.3	7.5	MKS4B042202F00	5.7	12.5	10.3	7.5	MKS4C041502F00
3.3 "	5.7	12.5	10.3	7.5	MKS4B043302F00	5	11	13	10	MKS4C041503F00
4.7 "	7.2	12.5	10.3	7.5	MKS4B044702G00	5	11	13	10	MKS4C042203F00
6.8 "	6	12	13	10	MKS4B044703G00	6	12.5	18	15	MKS4C042204C00
	6	12	13	10	MKS4B046802G00	6	12	13	10	MKS4C043303G00
	6	12	13	10	MKS4B046803G00	7	14	18	15	MKS4C043304D00
						7	14	18	15	MKS4C044704D00
						6	15	26.5	22.5	MKS4C044705B00
						8	15	18	15	MKS4C046804F00
						7	16.5	26.5	22.5	MKS4C046805D00
10 μ F	9	16	18	15	MKS4B051004J00	8.5	18.5	26.5	22.5	MKS4C051005F00
15 "	11	21	26.5	22.5	MKS4B051505I00	11	21	31.5	27.5	MKS4C051006B00
22 "	11	21	31.5	27.5	MKS4B052206B00	11	21	26.5	22.5	MKS4C051505I00
33 "	13	24	31.5	27.5	MKS4B053306D00	11	21	31.5	27.5	MKS4C051506B00
47 "	15	26	31.5	27.5	MKS4B054706F00	13	24	31.5	27.5	MKS4C052206D00
68 "	13	24	41.5	37.5	MKS4B054707C00	15	26	31.5	27.5	MKS4C053306F00
	20	39.5	31.5	27.5	MKS4B056806J00	17	29	31.5	27.5	MKS4C054706G00
	17	29	41.5	37.5	MKS4B056807E00	17	29	41.5	37.5	MKS4C054707E00
						20	39.5	31.5	27.5	MKS4C056806J00
						19	32	41.5	37.5	MKS4C056807F00
100 μ F	19	32	41.5	37.5	MKS4B061007F00	20	39.5	41.5	37.5	MKS4C061007G00
150 "	20	39.5	41.5	37.5	MKS4B061507G00	24	45.5	41.5	37.5	MKS4C061507H00
220 "	24	45.5	41.5	37.5	MKS4B062207H00					

* AC voltage: $f = 50 \text{ Hz}$; $1.4 \times U_{rms} + U_{DC} \leq U_r$

**PCM = Printed circuit module
= lead spacing

Dims. in mm.

ϕd	PCM	W
0.5	7.5	≤ 3
0.6	7.5	≥ 4
0.6	10	
0.8	15 - 27.5	
1.0	37.5	



Part number completion:

Tolerance: 20 % = M
10 % = K
5 % = J

Packing: bulk = S

Lead length: 6-2 = SD

Taped version see page 127.

Rights reserved to amend design data without prior notification.



Continuation

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

General Data

Capacitance	100 VDC/63 VAC*					250 VDC/160 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
0.01 μ F	2.5	7	10	7.5	MKS4D021002A00	3	8.5	10	7.5	MKS4F021002B00
	4	9	13	10	MKS4D021003C00	4	9	13	10	MKS4F021003C00
0.015 "	2.5	7	10	7.5	MKS4D021502A00	3	8.5	10	7.5	MKS4F021502B00
	4	9	13	10	MKS4D021503C00	4	9	13	10	MKS4F021503C00
0.022 "	2.5	7	10	7.5	MKS4D022202A00	3	8.5	10	7.5	MKS4F022202B00
	4	9	13	10	MKS4D022203C00	4	9	13	10	MKS4F022203C00
0.033 "	2.5	7	10	7.5	MKS4D023302A00	3	8.5	10	7.5	MKS4F023302B00
	4	9	13	10	MKS4D023303C00	4	9	13	10	MKS4F023303C00
0.047 "	2.5	7	10	7.5	MKS4D024702A00	3	8.5	10	7.5	MKS4F024702B00
	4	9	13	10	MKS4D024703C00	4	9	13	10	MKS4F024703C00
0.068 "	2.5	7	10	7.5	MKS4D026802A00	4	9	10	7.5	MKS4F026802C00
	4	9	13	10	MKS4D026803C00	4	9	13	10	MKS4F026803C00
0.1 μ F	2.5	7	10	7.5	MKS4D031002A00	4	9	10	7.5	MKS4F031002C00
	4	9	13	10	MKS4D031003C00	4	9	13	10	MKS4F031003C00
0.15 "	3	8.5	10	7.5	MKS4D031502B00	5	10.5	10.3	7.5	MKS4F031502E00
	4	9	13	10	MKS4D031503C00	4	9	13	10	MKS4F031503C00
0.22 "	3	8.5	10	7.5	MKS4D032202B00	5	10.5	10.3	7.5	MKS4F032202E00
	4	9	13	10	MKS4D032203C00	5	11	13	10	MKS4F032203F00
0.33 "	4	9	10	7.5	MKS4D033302C00	5.7	12.5	10.3	7.5	MKS4F033302F00
	4	9	13	10	MKS4D033303C00	5	11	13	10	MKS4F033303F00
0.47 "	4.5	9.5	10.3	7.5	MKS4D034702D00	6	12	13	10	MKS4F034703G00
	4	9	13	10	MKS4D034703C00	6	12.5	18	15	MKS4F034704C00
0.68 "	5	10.5	10.3	7.5	MKS4D036802E00	7	14	18	15	MKS4F036804D00
	4	9	13	10	MKS4D036803C00					
1.0 μ F	5.7	12.5	10.3	7.5	MKS4D041002F00	8	15	18	15	MKS4F041004F00
	5	11	13	10	MKS4D041003F00	6	15	26.5	22.5	MKS4F041005B00
1.5 "	6	12	13	10	MKS4D041503G00	9	16	18	15	MKS4F041504J00
	7	14	18	15	MKS4D041504D00	7	16.5	26.5	22.5	MKS4F041505D00
2.2 "	8	15	18	15	MKS4D042204F00	10.5	19	26.5	22.5	MKS4F042205G00
	6	15	26.5	22.5	MKS4D042205B00	9	19	31.5	27.5	MKS4F042206A00
3.3 "	9	16	18	15	MKS4D043304J00	11	21	26.5	22.5	MKS4F043305I00
	7	16.5	26.5	22.5	MKS4D043305D00	11	21	31.5	27.5	MKS4F043306B00
4.7 "	10.5	19	26.5	22.5	MKS4D044705G00	11	21	31.5	27.5	MKS4F044706B00
	9	19	31.5	27.5	MKS4D044706A00					
6.8 "	10.5	19	26.5	22.5	MKS4D046805G00	13	24	31.5	27.5	MKS4F046806D00
	11	21	31.5	27.5	MKS4D046806B00					
10 μ F	13	24	31.5	27.5	MKS4D051006D00	17	29	31.5	27.5	MKS4F051006G00
	13	24	31.5	27.5	MKS4D051506D00	17	34.5	31.5	27.5	MKS4F051506I00
22 "	15	26	31.5	27.5	MKS4D052206F00	17	29	41.5	37.5	MKS4F051507E00
	17	29	31.5	27.5	MKS4D053306G00	19	32	41.5	37.5	MKS4F052207F00
33 "	13	24	41.5	37.5	MKS4D053307C00	24	45.5	41.5	37.5	MKS4F053307H00
	17	29	41.5	37.5	MKS4D054707E00					
47 "	17	29	41.5	37.5	MKS4D054707E00					
	20	39.5	41.5	37.5	MKS4D056807G00					
100 μ F	24	45.5	41.5	37.5	MKS4D061007H00					

* AC voltage: $f = 50 \text{ Hz}$; $1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

**PCM = Printed circuit module = lead spacing

Dims. in mm.

Part number completion:

Tolerance: 20 % = M
 10 % = K
 5 % = J

Packing: bulk = S
 Lead length: 6-2 = SD

Taped version see page 127.

Rights reserved to amend design data without prior notification.

Continuation page 48



Continuation

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

General Data

Capacitance	400 VDC/200 VAC*					630 VDC/400 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
0.01 μ F	3	8.5	10	7.5	MKS4G021002B00_	3	8.5	10	7.5*	MKS4J021002B00_
	4	9	13	10	MKS4G021003C00_	4	9	13	10	MKS4J021003C00_
0.015 "	3	8.5	10	7.5	MKS4G021502B00_	4	9	10	7.5*	MKS4J021502C00_
	4	9	13	10	MKS4G021503C00_	4	9	13	10	MKS4J021503C00_
0.022 "	4	9	10	7.5	MKS4G022202C00_	4.5	9.5	10.3	7.5*	MKS4J022202D00_
	4	9	13	10	MKS4G022203C00_	4	9	13	10	MKS4J022203C00_
0.033 "	4	9	10	7.5	MKS4G023302C00_	5	10.5	10.3	7.5*	MKS4J023302E00_
	4	9	13	10	MKS4G023303C00_	5	11	13	10	MKS4J023303F00_
0.047 "	5	10.5	10.3	7.5	MKS4G024702E00_	5.7	12.5	10.3	7.5*	MKS4J024702F00_
	4	9	13	10	MKS4G024703C00_	6	12	13	10	MKS4J024703G00_
0.068 "	5	10.5	10.3	7.5	MKS4G026802E00_	6	12	13	10	MKS4J026803G00_
	4	9	13	10	MKS4G026803C00_	5	11	18	15	MKS4J026804B00_
0.1 μ F	5	10.5	10.3	7.5	MKS4G031002E00_	6	12.5	18	15	MKS4J031004C00_
	5	11	13	10	MKS4G031003F00_	6	15	26.5	22.5	MKS4J031005B00_
0.15 "	5.7	12.5	10.3	7.5	MKS4G031502F00_	7	14	18	15	MKS4J031504D00_
	6	12	13	10	MKS4G031503G00_	6	15	26.5	22.5	MKS4J031505B00_
0.22 "	6	12	13	10	MKS4G032203G00_	8	15	18	15	MKS4J032204F00_
	6	12.5	18	15	MKS4G032204C00_	6	15	26.5	22.5	MKS4J032205B00_
0.33 "	8	15	18	15	MKS4G033304F00_	7	16.5	26.5	22.5	MKS4J033305D00_
						9	19	31.5	27.5	MKS4J033306A00_
0.47 "	8	15	18	15	MKS4G034704F00_	10.5	19	26.5	22.5	MKS4J034705G00_
	6	15	26.5	22.5	MKS4G034705B00_	9	19	31.5	27.5	MKS4J034706A00_
0.68 "	7	16.5	26.5	22.5	MKS4G036805D00_	11	21	26.5	22.5	MKS4J036805I00_
						11	21	31.5	27.5	MKS4J036806B00_
1.0 μ F	10.5	19	26.5	22.5	MKS4G041005G00_	11	21	31.5	27.5	MKS4J041006B00_
	11	21	31.5	27.5	MKS4G041006B00_					
1.5 "	11	21	26.5	22.5	MKS4G041505I00_	15	26	31.5	27.5	MKS4J041506F00_
	11	21	31.5	27.5	MKS4G041506B00_					
2.2 "	11	21	31.5	27.5	MKS4G042206B00_	17	34.5	31.5	27.5	MKS4J042206I00_
						15	26	41.5	37.5	MKS4J042207D00_
3.3 "	13	24	31.5	27.5	MKS4G043306D00_	20	39.5	31.5	27.5	MKS4J043306J00_
						19	32	41.5	37.5	MKS4J043307F00_
4.7 "	17	29	31.5	27.5	MKS4G044706G00_	20	39.5	41.5	37.5	MKS4J044707G00_
6.8 "	17	34.5	31.5	27.5	MKS4G046806I00_	24	45.5	41.5	37.5	MKS4J046807H00_
	15	26	41.5	37.5	MKS4G046807D00_					
10 μ F	19	32	41.5	37.5	MKS4G051007F00_					
15 "	20	39.5	41.5	37.5	MKS4G051507G00_					

* AC voltage: $f = 50 \text{ Hz}; 1.4 \times U_{\text{rms}} + \text{UDC} \leq U_r$

**PCM = Printed circuit module = lead spacing

* Admissible AC voltage 250 VAC max.

Dims. in mm.

Part number completion:

Tolerance: 20 % = M

10 % = K

5 % = J

Packing: bulk = S

Lead length: 6-2 = SD

Taped version see page 127.

Rights reserved to amend design data without prior notification.

Continuation page 49

Continuation

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

General Data

Capacitance	1000 VDC/400 VAC*					1500 VDC/400 VAC*				
	W	H	L	PCM**	Part number	W	H	L	PCM**	Part number
1000 pF	3	8.5	10	7.5	MKS4O111002B00	4	9	13	10	MKS4S011003C00
	4	9	13	10	MKS4O111003C00					
1500 "	3	8.5	10	7.5	MKS4O111502B00	4	9	13	10	MKS4S011503C00
	4	9	13	10	MKS4O111503C00					
2200 "	3	8.5	10	7.5	MKS4O112202B00	4	9	13	10	MKS4S012203C00
	4	9	13	10	MKS4O112203C00					
3300 "	4	9	10	7.5	MKS4O113302C00	4	9	13	10	MKS4S013303C00
	4	9	13	10	MKS4O113303C00					
4700 "	4	9	10	7.5	MKS4O114702C00	4	9	13	10	MKS4S014703C00
	4	9	13	10	MKS4O114703C00					
6800 "	4.5	9.5	10.3	7.5	MKS4O116802D00	5	11	13	10	MKS4S016803F00
	4	9	13	10	MKS4O116803C00					
0.01 μF	5	10.5	10.3	7.5	MKS4O121002E00	6	12	13	10	MKS4S021003G00
	5	11	13	10	MKS4O121003F00					
0.015 "	5.7	12.5	10.3	7.5	MKS4O121502F00	6	12.5	18	15	MKS4S021504C00
	6	12	13	10	MKS4O121503G00					
0.022 "	5	11	18	15	MKS4O122204B00	7	14	18	15	MKS4S022204D00
0.033 "	6	12.5	18	15	MKS4O123304C00	8	15	18	15	MKS4S023304F00
	6	15	26.5	22.5	MKS4O123305B00					
0.047 "	7	14	18	15	MKS4O124704D00	7	16.5	26.5	22.5	MKS4S024705D00
	6	15	26.5	22.5	MKS4O124705B00					
0.068 "	8	15	18	15	MKS4O126804F00	8.5	18.5	26.5	22.5	MKS4S026805F00
	6	15	26.5	22.5	MKS4O126805B00					
0.1 μF	9	16	18	15	MKS4O131004J00	10.5	19	26.5	22.5	MKS4S031005G00
	7	16.5	26.5	22.5	MKS4O131005D00					
0.15 "	8.5	18.5	26.5	22.5	MKS4O131505F00	11	21	31.5	27.5	MKS4S031506B00
	10.5	19	26.5	22.5	MKS4O132205G00					
0.22 "	11	21	26.5	22.5	MKS4O133305I00	17	34.5	31.5	27.5	MKS4S033306I00
	11	21	31.5	27.5	MKS4O133306B00					
0.47 "	13	24	31.5	27.5	MKS4O134706D00	20	39.5	31.5	27.5	MKS4S034706J00
0.68 "	15	26	31.5	27.5	MKS4O136806F00	20	39.5	41.5	37.5	MKS4S036807G00
1.0 μF	17	29	31.5	27.5	MKS4O141006G00	24	45.5	41.5	37.5	MKS4S041007H00
	17	29	41.5	37.5	MKS4O141007E00					
1.5 "	19	32	41.5	37.5	MKS4O141507F00					
	20	39.5	41.5	37.5	MKS4O142207G00					
2.2 "	24	45.5	41.5	37.5	MKS4O143307H00					
3.3 "										

* AC voltage: $f = 50 \text{ Hz}; 1.4 \times U_{\text{rms}} + U_{\text{DC}} \leq U_r$

** PCM = Printed circuit module = lead spacing

Dims. in mm.

Part number completion:

Tolerance: 20 % = M

10 % = K

5 % = J

Packing: bulk = S

Lead length: 6-2 = SD

Taped version see page 127.

Rights reserved to amend design data without prior notification.

Continuation page 50



Continuation

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

General Data

Capacitance	2000 VDC/400 VAC*				
	W	H	L	PCM**	Part number
1000 pF	4	9	13	10	MKS4U011003C00_
1500 "	4	9	13	10	MKS4U011503C00_
2200 "	5	11	13	10	MKS4U012203F00_
3300 "	6	12	13	10	MKS4U013303H00_
	5	11	18	15	MKS4U013304B00_
4700 "	5	11	18	15	MKS4U014704B00_
6800 "	6	12.5	18	15	MKS4U016804C00_
0.01 μF	7	14	18	15	MKS4U021004D00_
	6	15	26.5	22.5	MKS4U021005B00_
0.015 "	6	15	26.5	22.5	MKS4U021505B00_
0.022 "	7	16.5	26.5	22.5	MKS4U022205D00_
0.033 "	10.5	19	26.5	22.5	MKS4U023305G00_
0.047 "	11	21	26.5	22.5	MKS4U024705I00_
	11	21	31.5	27.5	MKS4U024706B00_
0.068 "	11	21	31.5	27.5	MKS4U026806B00_
0.1 μF	13	24	31.5	27.5	MKS4U031006D00_
0.15 "	17	29	31.5	27.5	MKS4U031506G00_
	13	24	41.5	37.5	MKS4U031507C00_
0.22 "	17	29	41.5	37.5	MKS4U032207E00_
0.33 "	20	39.5	41.5	37.5	MKS4U033307G00_
0.47 "	24	45.5	41.5	37.5	MKS4U034707H00_

The values of the WIMA MKM 4 ranges according to the main catalogue 2009 are still available on request.

Part number completion:

Tolerance: 20 % = M
 10 % = K
 5 % = J
 Packing: bulk = S
 Lead length: 6-2 = SD
 Taped version see page 127.


* AC voltage: $f = 50 \text{ Hz}$; $1.4 \times U_{\text{rms}} + \text{UDC} \leq U_r$

** PCM = Printed circuit module = lead spacing

Dims. in mm.

Rights reserved to amend design data without prior notification.

Permissible AC voltage in relation to frequency at 10° C internal temperature rise (general guide).





Recommendation for Processing and Application of Through-Hole Capacitors

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

Soldering Process

A preheating of through-hole WIMA capacitors is allowed for temperatures $T_{max} < 100^{\circ}C$.
 In practice a preheating duration of $t < 5$ min. has been proven to be best.


Single wave soldering

Soldering bath temperature: $T < 260^{\circ}C$
 Immersion time: $t < 5$ sec

Double wave soldering

Soldering bath temperature: $T < 260^{\circ}C$
 Immersion time: $2 \times t < 3$ sec

Due to different soldering processes and heat requirements the graphs are to be regarded as a recommendation only.



WIMA Quality and Environmental Philosophy

ISO 9001:2000 Certification

ISO 9001:2000 is an international basic standard of quality assurance systems for all branches of industry. The approval according to ISO 9001:2000 of our factories by the VDE inspectorate certifies that organisation, equipment and monitoring of quality assurance in our factories correspond to internationally recognized standards.

WIMA WPCS

The WIMA Process Control System (WPCS) is a quality surveillance and optimization system developed by WIMA. WPCS is a major part of the quality-oriented WIMA production. Points of application of WPCS during production process:

- incoming material inspection
- metallization
- film inspection
- schoopage
- pre-healing
- lead attachment
- cast resin preparation/encapsulation
- 100% final inspection
- AQL check

WIMA Environmental Policy

All WIMA capacitors, irrespective of whether through-hole devices or SMD, are made of environmentally friendly materials. Neither during manufacture nor in the product itself any toxic substances are used, e.g.

- Lead
- PCB
- CFC
- Hydrocarbon chloride
- Chromium 6+
- PBB/PBDE
- Arsenic
- Cadmium
- Mercury
- etc.

We merely use pure, recyclable materials for packing our components, such as:

- carton
- cardboard
- adhesive tape made of paper
- polystyrene

We almost completely refrain from using packing materials such as:

- foamed polystyrene (Styropor®)
- adhesive tapes made of plastic
- metal clips

RoHS Compliance

According to the RoHS Directive 2002/95/EC certain hazardous substances like e.g. lead, cadmium, mercury must not be used any longer in electronic equipment as of July 1st, 2006. For the sake of the environment WIMA has refrained from using such substances since years already.



WIMA Kondensatoren sind bleifrei konform RoHS 2002/95/EG

WIMA capacitors are lead free in accordance with RoHS 2002/95/EC

Tape for lead-free WIMA capacitors

DIN EN ISO 14001:2005

WIMA's environmental management has been established in accordance with the guidelines of DIN EN ISO 14001:2005. The certification has been granted in June 2006.

Typical Dimensions for Taping Configuration



勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)




Diagram 1:
PCM 2.5/5/7.5mm




Diagram 2: PCM 10/15 mm

Diagram 3: PCM 22.5 and 27.5*mm
*PCM 27.5 tapping possible with two feed holes between components

Designation	Symbol	Dimensions for Radial Taping							
		PCM 2.5 tapping	PCM 5 tapping	PCM 7.5 tapping	PCM 10 tapping*	PCM 15 tapping*	PCM 22.5 tapping	PCM 27.5 tapping	
Carrier tape width	W	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	18.0 ±0.5	
Hold-down tape width	W ₀	6.0 for hot-sealing adhesive tape	6.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	12.0 for hot-sealing adhesive tape	
Hole position	W ₁	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	9.0 ±0.5	
Hold-down tape position	W ₂	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	0.5 to 3.0 max.	
Feed hole diameter	D ₀	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	4.0 ±0.2	
Pitch of component	P	12.7 ±1.0	12.7 ±1.0	12.7 ±1.0	25.4 ±1.0	25.4 ±1.0	38.1 ±1.5	38.1 ±1.5 or 50.8 ±1.5	
Feed hole pitch	P ₀	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	12.7 ±0.3 cumulative pitch error max. 1.0 mm/20 pitch	
Feed hole centre to lead	P ₁	5.1 ±0.5	3.85 ±0.7	2.6 ±0.7	7.7 ±0.7	5.2 ±0.7	7.8 ±0.7	5.3 ±0.7	
Hole centre to component centre	P ₂	6.35 ±1.3	6.35 ±1.3	6.35 ±1.3	12.7 ±1.3	12.7 ±1.3	19.05 ±1.3	19.05 ±1.3	
Feed hole centre to bottom edge of the component	H	16.5 ±0.3 18.5 ±0.5	16.5 ±0.3 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	16.5 ±0.5 18.5 ±0.5	
Feed hole centre to top edge of the component	H ₁	H+H _{component} < H ₁ 32.25 max.	H+H _{component} < H ₁ 32.25 max.	H+H _{component} < H ₁ 24.5 to 31.5	H+H _{component} < H ₁ 25.0 to 31.5	H+H _{component} < H ₁ 26.0 to 37.0	H+H _{component} < H ₁ 30.0 to 43.0	H+H _{component} < H ₁ 35.0 to 45.0	
Lead spacing at upper edge of carrier tape	F	2.5 ±0.5	5.0 ^{+0.8} _{-0.2}	7.5 ±0.8	10.0 ±0.8	15 ±0.8	22.5 ±0.8	27.5 ±0.8	
Lead diameter	d	0.4 ±0.05	0.5 ±0.05	0.5 ±0.05 or 0.6 ^{+0.06} _{-0.05}	0.5 ±0.05 or 0.6 ^{+0.06} _{-0.05}	0.8 ^{+0.08} _{-0.05}	0.8 ^{+0.08} _{-0.05}	0.8 ^{+0.08} _{-0.05}	
Component alignment	Δh	± 2.0 max.	± 2.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	± 3.0 max.	
Total tape thickness	t	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	0.7 ±0.2	
Package (see also page 128)	ROLL/AMMO				AMMO				
	REEL	φ 360 max. φ 30 ±1	B 52 ±2 B 58 ±2	} depending on comp. dimensions		REEL	φ 360 max. φ 30 ±1	B 52 ±2 B 58 ±2 B 66 ±2	} depending on PCM and component dimensions
Unit	see details page 130.								

Dims in mm.

* Diameter of leads see General Data.

* PCM 10 and PCM 15 can be crimped to PCM 7.5.

Position of components according to PCM 7.5 (sketch 11). P₀ = 12.7 or 15.0 is possible

Please clarify customer-specific deviations with the manufacturer.



Packing Quantities for Bulk Capacitors and TPS*

PCM	Size				pcs. per packaging unit bulk			pcs. per packaging unit/TPS*	
	W	H	L	Codes	Mini M	Standard S	Maxi G	Mini X	Standard Y
2.5 mm	2.5	7	4.6	0B	1000	5000	10000	-	-
	3	7.5	4.6	0C	1000	5000	10000	-	-
	3.8	8.5	4.6	0D	1000	5000	10000	-	-
	4.6	9	4.6	0E	1000	5000	10000	-	-
	5.5	10	4.6	0F	1000	5000	10000	-	-
5 mm	2.5	6.5	7.2	1A	2000	5000	10000	-	-
	3	7.5	7.2	1B	1000	5000	-	-	-
	3.5	8.5	7.2	1C	1000	5000	-	-	-
	4.5	6	7.2	1D	1000	6000	-	-	-
	4.5	9.5	7.2	1E	1000	4000	-	-	-
	5	10	7.2	1F	1000	3500	-	-	-
	5.5	7	7.2	1G	1000	4000	-	-	-
	5.5	11.5	7.2	1H	500	2500	-	-	-
	6.5	8	7.2	1I	1000	2500	-	-	-
	7.2	8.5	7.2	1J	500	2500	-	-	-
	7.2	13	7.2	1K	500	2000	-	-	-
8.5	10	7.2	1L	500	2000	-	-	-	
8.5	14	7.2	1M	500	1500	-	-	-	
11	16	7.2	1N	250	1000	-	-	-	
7.5 mm	2.5	7	10	2A	1000	5000	-	-	-
	3	8.5	10	2B	1000	5000	-	-	-
	4	9	10	2C	1000	4000	-	-	-
	4.5	9.5	10.3	2D	1000	3500	-	-	-
	5	10.5	10.3	2E	1000	3000	-	-	-
	5.7	12.5	10.3	2F	500	2000	-	-	-
	7.2	12.5	10.3	2G	500	1500	-	-	-
10 mm	3	9	13	3A	1000	3000	-	-	-
	4	8.5	13.5	3A	500	3000	-	-	-
	4	9	13	3C	1000	3000	-	-	-
	4	9.5	13	3D	1000	3000	-	-	-
	5	10	13.5	3B	500	2000	-	-	-
	5	11	13	3F	1000	3000	-	-	-
	6	12	13	3G	800	2400	-	-	-
6	12.5	13	3H	800	2400	-	-	-	
8	12	13	3I	500	2000	-	-	-	
15 mm	5	11	18	4B	800	2400	-	-	-
	5	13	19	FC	200	1000	-	-	-
	6	12.5	18	4C	500	2000	-	-	-
	6	14	19	FD	250	1000	-	-	-
	7	14	18	4D	400	1600	-	-	-
	7	15	19	FE	250	1000	-	-	-
	8	15	18	4F	400	1200	-	-	-
	8	17	19	FF	100	500	-	-	-
	9	14	18	4H	400	1200	-	-	-
	9	16	18	4J	300	900	-	-	-
	10	18	19	FG	100	500	-	-	-
11	14	18	4M	300	1000	-	-	-	
22.5 mm	5	14	26.5	5A	300	1200	-	-	-
	6	15	26.5	5B	250	1000	-	-	-
	7	16.5	26.5	5D	190	760	-	-	-
	8	20	28	FH	125	500	-	-	-
	8.5	18.5	26.5	5F	125	500	-	-	-
	10	22	28	FI	-	-	-	90	540
	10.5	19	26.5	5G	-	-	-	170	680
	10.5	20.5	26.5	5H	-	-	-	170	680
	11	21	26.5	5I	-	-	-	170	680
12	24	28	FJ	-	-	-	75	450	
27.5 mm	9	19	31.5	6A	-	-	-	160	640
	11	21	31.5	6B	-	-	-	136	544
	13	24	31.5	6D	-	-	-	112	448
	13	25	33	FK	-	-	-	56	336
	15	26	31.5	6F	-	-	-	96	384
	15	26	33	FL	-	-	-	48	288
	17	29	31.5	6G	-	-	-	88	176
	17	34.5	31.5	6I	-	-	-	88	176
	20	32	33	FM	-	-	-	36	216
20	39.5	31.5	6J	-	-	-	36	144	
37.5 mm	9	19	41.5	7A	-	-	-	60	480
	11	22	41.5	7B	-	-	-	51	408
	13	24	41.5	7C	-	-	-	84	252
	15	26	41.5	7D	-	-	-	72	144
	17	29	41.5	7E	-	-	-	66	132
	19	32	41.5	7F	-	-	-	54	108
	20	39.5	41.5	7G	-	-	-	27	108
	24	45.5	41.5	7H	-	-	-	21	84



**Packing Units for Taped Capacitors
 with Radial Leads**

PCM	Size				ROLL		REEL				AMMO			
					H16.5	H18.5	ø 360		ø 500		340 x 340		490 x 370	
	W	H	L	Codes	N	O	F	I	H	J	A	C	B	D
2.5 mm	2.5	7	4.6	0B	2200		2500		-		2800		-	
	3	7.5	4.6	0C	2000		2300		-		2300		-	
	3.8	8.5	4.6	0D	1500		1800		-		1800		-	
	4.6	9	4.6	0E	1200		1500		-		1500		-	
	5.5	10	4.6	0F	900		1200		-		1200		-	
	5 mm	2.5	6.5	7.2	1A	2200		2500		-		2800		-
3		7.5	7.2	1B	2000		2300		-		2300		-	
3.5		8.5	7.2	1C	1600		2000		-		2000		-	
4.5		6	7.2	1D	1300		1500		-		1500		-	
4.5		9.5	7.2	1E	1300		1500		-		1500		-	
5		10	7.2	1F	1100		1400		-		1400		-	
5.5		7	7.2	1G	1000		1200		-		1200		-	
5.5		11.5	7.2	1H	1000		1200		-		1200		-	
6.5		8	7.2	1I	800		1000		-		1000		-	
7.2		8.5	7.2	1J	700		1000		-		1000		-	
7.2		13	7.2	1K	700		950		-		1000		-	
8.5		10	7.2	1L	600		800		-		800		-	
8.5		14	7.2	1M	600		800		-		800		-	
11		16	7.2	1N	500		700		-		700		-	
7.5 mm	2.5	7	10	2A	-		2500		4400		2500		-	
	3	8.5	10	2B	-		2200		4300		2300		4150	
	4	9	10	2C	-		1700		3200		1700		3100	
	4.5	9.5	10.3	2D	-		1500		2900		1400		2800	
	5	10.5	10.3	2E	-		1300		2500		1300		-	
	5.7	12.5	10.3	2F	-		1000		2200		1100		-	
	7.2	12.5	10.3	2G	-		900		1800		1000		-	
10 mm	3	9	13	3A	-		1100		2200		-		1900	
	4	8.5	13.5	FA	-		900		1600		-		1450	
	4	9	13	3C	-		900		1600		-		1450	
	4	9.5	13	3D	-		900		1600		-		1400	
	5	10	13.5	FB	-		700		1300		-		1200	
	5	11	13	3F	-		700		1300		-		1200	
	6	12	13	3G	-		550		1100		-		1000	
	6	12.5	13	3H	-		550		1100		-		1000	
8	12	13	3I	-		400		800		-		740		
15 mm	5	11	18	4B	-		600		1200		-		1150	
	5	13	19	FC	-		600		1200		-		1200	
	6	12.5	18	4C	-		500		1000		-		1000	
	6	14	19	FD	-		500		1000		-		1000	
	7	14	18	4D	-		450		900		-		850	
	7	15	19	FE	-		450		900		-		850	
	8	15	18	4F	-		400		800		-		740	
	8	17	19	FF	-		400		800		-		740	
	9	14	18	4H	-		350		700		-		650	
	9	16	18	4J	-		350		700		-		650	
	10	18	19	FG	-		300		650		-		590	
11	14	18	4M	-		300		600		-		540		
22.5 mm	5	14	26.5	5A	-		-		800		-		770	
	6	15	26.5	5B	-		-		700		-		640	
	7	16.5	26.5	5D	-		-		600		-		550	
	8	20	28	FH	-		-		500		-		480	
	8.5	18.5	26.5	5F	-		-		480		-		450	
	10	22	28	FI	-		-		420		-		380	
	10.5	19	26.5	5G	-		-		400		-		360	
	10.5	20.5	26.5	5H	-		-		400		-		360	
	11	21	26.5	5I	-		-		380		-		350	
	12	24	28	FJ	-		-		350		-		310	
27.5 mm	9	19	31.5	6A	-		-		460/340*		-		420	
	11	21	31.5	6B	-		-		380/280*		-		350	
	13	24	31.5	6D	-		-		300		-		290	
	15	26	31.5	6F	-		-		270		-		250	

* for 2-inch transport pitches.
 Samples and pre-production needs 1 packing unit minimum.

■ Moulded versions.

Rights reserved to amend design data without prior notification.



A WIMA part number consists of 18 digits and is composed as follows:

- Field 1 - 4: Type description
- Field 5 - 6: Rated voltage
- Field 7 - 10: Capacitance
- Field 11 - 12: Size and PCM
- Field 13 - 14: Special features (e.g. Snubber versions)
- Field 15: Capacitance tolerance
- Field 16: Packing
- Field 17 - 18: Lead length (untaped)

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
M	K	S	2	C	0	2	1	0	0	1	A	0	0	M	S	S	D
MKS 2				63 VDC		0.01 µF			2.5x6.5x7.2		-		20%	bulk	6-2		

<p>Type description:</p> <p>SMD-PET = SMDT SMD-PPS = SMDI FKP 02 = FKP0 MKS 02 = MKS0 FKS 2 = FKS2 FKP 2 = FKP2 MKS 2 = MKS2 MKP 2 = MKP2 FKS 3 = FKS3 FKP 3 = FKP3 MKS 4 = MKS4 MKP 4 = MKP4 MKP 10 = MKP1 FKP 4 = FKP4 FKP 1 = FKP1 MKP-X2 = MKX2 MKP-X2 R = MKXR MKP-Y2 = MKY2 MP 3-X2 = MPX2 MP 3-X1 = MPX1 MP 3-Y2 = MPY2 MP 3R-Y2 = MPRY Snubber MKP = SNMP Snubber FKP = SNFP GTO MKP = GTOM DC-LINK MKP 4 = DCP4 DC-LINK MKP C = DCPC DC-LINK HC = DCH_ SuperCap C = SCSC SuperCap MC = SMC SuperCap R = SCSR SuperCap MR = SCMR</p>	<p>Rated voltage:</p> <p>2.5 VDC = A1 4 VDC = A2 14 VDC = A3 28 VDC = A4 40 VDC = A5 5 VDC = A6 50 VDC = B0 63 VDC = C0 100 VDC = D0 160 VDC = E0 250 VDC = F0 400 VDC = G0 450 VDC = H0 600 VDC = I0 630 VDC = J0 700 VDC = K0 800 VDC = L0 850 VDC = M0 900 VDC = N0 1000 VDC = O1 1100 VDC = P0 1200 VDC = Q0 1250 VDC = R0 1500 VDC = S0 1600 VDC = T0 2000 VDC = U0 2500 VDC = V0 3000 VDC = W0 4000 VDC = X0 6000 VDC = Y0 275 VAC = 0W 275 VAC = 1W 300 VAC = 2W 400 VAC = 3W 440 VAC = 4W 500 VAC = 5W</p>	<p>Capacitance:</p> <p>22 pF = 0022 47 pF = 0047 100 pF = 0100 150 pF = 0150 220 pF = 0220 330 pF = 0330 470 pF = 0470 680 pF = 0680 1000 pF = 1100 1500 pF = 1150 2200 pF = 1220 3300 pF = 1330 4700 pF = 1470 6800 pF = 1680 0.01 µF = 2100 0.022 µF = 2220 0.047 µF = 2470 0.1 µF = 3100 0.22 µF = 3220 0.47 µF = 3470 1 µF = 4100 2.2 µF = 4220 4.7 µF = 4470 10 µF = 5100 22 µF = 5220 47 µF = 5470 100 µF = 6100 220 µF = 6220 1 F = A010 2.5 F = A025 50 F = A500 100 F = B100 110 F = B110 600 F = B600 1200 F = C120 ...</p>	<p>Size:</p> <p>4.8x3.3x3 Size 1812 = X1 4.8x3.3x4 Size 1812 = X2 5.7x5.1x3.5 Size 2220 = Y1 5.7x5.1x4.5 Size 2220 = Y2 7.2x6.1x3 Size 2824 = T1 7.2x6.1x5 Size 2824 = T2 10.2x7.6x5 Size 4030 = K1 12.7x10.2x6 Size 5040 = V1 15.3x13.7x7 Size 6054 = Q1 2.5x7x4.6 PCM2.5 = 0B 3x7.5x4.6 PCM2.5 = 0C 2.5x6.5x7.2 PCM5 = 1A 3x7.5x7.2 PCM5 = 1B 2.5x7x10 PCM7.5 = 2A 3x8.5x10 PCM7.5 = 2B 3x9x13 PCM10 = 3A 4x9x13 PCM10 = 3C 5x11x18 PCM15 = 4B 6x12.5x18 PCM15 = 4C 5x14x26.5 PCM22.5 = 5A 6x15x26.5 PCM22.5 = 5B 9x19x31.5 PCM27.5 = 6A 11x21x31.5 PCM27.5 = 6B 9x19x41.5 PCM37.5 = 7A 11x22x41.5 PCM37.5 = 7B 94x49x182 DCH_ = H0 94x77x182 DCH_ = H1 ...</p> <p>Special features:</p> <p>Standard = 00 Version A1 = 1A Version A1.1.1 = 1B Version A1.2 = 1C ...</p>	<p>Tolerance:</p> <p>20% = M 10% = K 5% = J 2.5% = H 1% = E ...</p> <p>Packing:</p> <p>AMMO H16.5 340x340 = A AMMO H16.5 490x370 = B AMMO H18.5 340x340 = C AMMO H18.5 490x370 = D REEL H16.5 360 = F REEL H16.5 500 = H REEL H18.5 360 = I REEL H18.5 500 = J ROLL H16.5 = N ROLL H18.5 = O BLISTER W12 180 = P BLISTER W12 330 = Q BLISTER W16 330 = R BLISTER W24 330 = T Bulk Mini = M Bulk Standard = S Bulk Maxi = G TPS Mini = X TPS Standard = Y ...</p> <p>Lead length (untaped)</p> <p>3.5±0.5 = C9 6-2 = SD 16±1 = P1 ...</p>
--	--	---	--	--

The data on this page is not complete and serves only to explain the part number system. Part number information is listed on the pages of the respective WIMA range.