

151381	SMA-J+杜邦(F)-0.5M	SMA 轉杜邦線母-轉接線-SMA 公-杜邦母-0.5M
151383	SMA-J+杜邦(F)-1M	SMA 轉杜邦線母-轉接線-SMA 公-杜邦母-1M
151384	SMA-K+杜邦(F)-0.5M	SMA 轉杜邦線母-轉接線-SMA 母-杜邦母-0.5M
151385	SMA-K+杜邦(F)-1M	SMA 轉杜邦線母-轉接線-SMA 母-杜邦母-1M
151386	SMA-JW+杜邦(F)-0.5M	SMA 轉杜邦線母-轉接線-SMA 彎公-杜邦母-0.5M
151387	SMA-JW+杜邦(F)-1M	SMA 轉杜邦線母-轉接線-SMA 彎公-杜邦母-1M
151388	SMA-KW+杜邦(F)-0.5M	SMA 轉杜邦線母-轉接線-SMA 彎母-杜邦母-0.5M
151389	SMA-KW+杜邦(F)-1M	SMA 轉杜邦線母-轉接線-SMA 彎母-杜邦母-1M



SMA公頭 轉 杜邦母



SMA母頭 轉 杜邦母



SMA彎公 轉 杜邦母



SMA彎母 轉 杜邦母



SMA公头



SMA母头



SMA弯公



SMA弯母

# 产品规格书

This document contains proprietary information and such information may not be disclosed to others for any purposes,  
 本文件包含专有信息，不得出于任何目的向他人披露此类信息。  
 not used for sales/marketing/procurement purposes without written permission.  
 未经书面许可，不得用于销售/营销/采购目的。

- 1. Electrical/电气
  - 1.1 Impedance /阻抗 50Ω
  - 1.2 Frequency /频率 DC-6GHz
  - 1.3 VSWR/驻波 ≤1.2
  - 1.4 Dielectric withstanding voltage /介质耐压 1000V(rms)
  - 1.5 Center contact resistance /中心接触电阻 ≤3MΩ
  - 1.6 Outer contact resistance /外部接触电阻 ≤2MΩ
  - 1.7 Insulation resistance /绝缘电阻 ≥5000MΩ

- 2. Environmenta & Mechanical/环境与机械
  - 2.1 Temperature range/温度范围 -45°~+125°
  - 2.2 Rohs Compliant/符合RoHS
  - 2.3 Durability/耐久性 500cycles

- 3. Material and Plating/材料和电镀
  - 3.1 Inner Contact/内导体: Phosphorus-Copper Gold Plating/磷铜镀金
  - 3.2 Outer Contact/外导体: Brass, Gold plated/黄铜镀金
  - 3.3 Insulators/绝缘体: PTFE/聚四氟乙烯

