

勝 特 力 材 料 886-3-5753170
胜特力电子(上海) 86-21-54151736
胜特力电子(深圳) 86-755-83298787
Http://www.100y.com.tw







P. C. BOARD LAYOUT

DIMENSIONS

CIRCUITS	DIM. A	DIM. B	DIM. C
6	5.08	7.96	10.16
8	7.62	10.50	12.70
10	10.16	13.04	15.24
12	12.70	15.58	17.78
14	15.24	18.12	20.32
16	17.78	20.66	22.86
18	20.32	23.20	25.40
20	22.86	25.74	27.94
22	25.40	28.28	30.48
24	27.94	30.82	33.02
26	30.48	33.36	35.56
28	33.02	35.90	38.10
30	35.56	38.44	40.64
32	38.10	40.98	43.18
34	40.64	43.52	45.72
36	43.18	46.06	48.26
38	45.72	48.60	50.80
40	48.26	51.14	53.34

MATERIAL:
BASE: PBT 94V-0 (BLACK COLOR)
PIN : BRASS
SELECT GOLD FLASH: GOLD-FLASH ON CONTACT AREA B
TIN-PLATED ON SOLDER AREA

ORDER INFORMATION:

2581P XX 0 3 X

CIRCUITS NO.

MATERIAL:
3=PBT 94V-0

PLATING:
A=SELECT GOLD FLASH
1=GOLD FLASH
T=TIN-PLATED
B

MATERIAL: SEE NOTE B
FINISH(COLOR): SEE NOTE B
FILE NAME:

REV.	REVISION RECORD	ECN NO.	DATE
B	ADD PLATING	960807	2007/08/29
A	NEW RELEASE		2002/3/13

SCALE: FREE
SHEET: 1 OF 1
DRAWN BY: David 2007/8/29
UNIT: mm
REV.: B
APPROVED BY:
DRAW NO.: B (CQ) 2581PXX03X
GENERAL TOLERANCE:
ANGLE: ±3°
DIM: x. ±0.5, x.x ±0.25, x.xx ±0.12, x.xxx ±0.08
TITLE: 2.54mm DUAL ROW STRAIGHT HEADER