






SPECIFICATIONS:

Material:

Insulator: PBT, rated UL94V-0

Insulator: Color Black

Contacts: Brass

Plating:

Gold Flash over Nickel underplate overall

Electrical:

Operating voltage: 250 VAC max

Current rating: 1 Amp max

Contact resistance: 20 mohms max

Insulation resistance:

5,000 Mohms min 500 VDC

Dielectric withstanding voltage:

1,000 VAC for 1 minute

Temperatruue Rating:

Operating temperature: -55° to +105°

Environmental:


Lead free, RoHS compliant

Recommended soldering temp:

200° for 5 seconds

勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>

Recommended PCB Layout



POSITION	A	B	C
10	10.16	32.00	21.84
14	15.24	37.08	26.92
16	17.78	39.62	29.46
20	22.86	44.70	34.54
24	27.94	49.78	39.62
26	30.48	52.32	42.16
30	35.56	57.40	47.24
34	40.64	62.48	52.32
40	48.26	70.10	59.94
50	60.96	82.80	72.64
60	73.66	95.50	85.34
64	78.74	100.58	90.42

勾勾牛角2.54 / 180°
全金 / 長耳 / Dip8

SCALE: AS SHOWN

UNIT: mm

DRAWN HBK

109 / 12 / 07

CHECKED

/ /

APPROVED

/ /

02-

DRAWN NAME:

MLA2XXA800



SIZE

A4

E

A