

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 03/11/11'		

NOTES:

1. MATERIAL

- 1.1 INSULATOR:THERMOPLASTIC(UL 94V-0).
- 1.2 CONTACT: COPPER ALLOY.

2. SPECIFICATION

- 2.1 TEMPERATURE RANGE:-40°C~+105°C.
- 2.2 CONTACT RESISTANCE:30mΩ max.
- 2.3 INSULATION RESISTANCE:1000MΩ min.
- 2.4 DIELECTRIC WITHSTANDING VOLTAGE:AC 500V PER MINUTE.

3. PRODUCT NUMBER CODE:

DS1015-02- X X X

CONTACT PLATING
2: NICKEL+GOLD FLASH
6: FULL TIN
8: FULL GOLD FLASH

HOUSING COLOR
R:RED

No. OF CONTACTS
04 06 08 10
12 14 16 18
20 24

COVER

HOUSING

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE
X.	±0.60	X.	±5°	UNITS	mm	MICRO MATCH PADDEL BOARD CONNECTOR
.X	±0.38	.X	±3°	SHEET SIZE	A4	
.XX	±0.25	.XX	±2°			SERIES DS1015-02 SERIES
DRAWING TYPE		CUSTOMER				
SCALE		1:1	SHEET 1 OF 1			
DRAWING NO.		C-DS1015-02-XXX				

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)