




REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	DGQ 06/14/11'		LJC 06/14/11'
B	ADD P/N CODE	JLZ 01/04/15'		LJC 01/04/15'
C	PACKING TYPE CHANGE	JLZ 02/10/15'		




勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

NOTES:


- MATERIAL
 - INSULATOR:THERMOPLASTIC(UL 94V-0).
 - CONTACT: 0.25t COPPER ALLOY.
- SPECIFICATION
 - TEMPERATURE RANGE:-40°C~+105°C.
 - CONTACT RESISTANCE:30mΩ max.
 - INSULATION RESISTANCE:1000MΩ min.
 - DIELECTRIC WITHSTANDING VOLTAGE:AC 500V PER MINUTE.

- PRODUCT NUMBER CODE:
 DS1015-04 - X X X X X

PACKING TYPE (C)
 B: Tube
 R: TAPE ON REEL
 MYLAR SUPPORT (B)
 S: W/ MYLAR
 X: W/O MYLAR
 CONTACT PLATING
 6: FULL MATT TIN
 HOUSING COLOR
 R: RED
 No. OF CONTACTS
 04 06 08 10 12 14
 16 18 20 22 24




POSITIONS	DIM A	DIM B	DIM C
4	6.96	5.46	3.81
6	9.50	8.00	6.35
8	12.04	10.54	8.89
10	14.58	13.08	11.43
12	17.12	15.62	13.97
14	19.66	18.16	16.51
16	22.20	20.70	19.05
18	24.74	23.24	21.59
20	27.28	25.78	24.13
22	29.82	28.32	26.67
24	32.36	30.86	29.21




CONTACT
ROW-DISTANCE

2.54
1.27



2.54±0.05
1.27±0.05



RECOMMEND PCB LAYOUT
(COMPONENT SIDE OF BOARD SHOWN)

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE	
X.	±0.60	X.	±5°	UNITS	mm	MICRO MATCH FEMALE VERTICAL THROUGH HOLE TYPE	
.X	±0.38	.X	±3°	SHEET SIZE	A4		
.XX	±0.25	.XX	±2°	SERIES DS1015-04 SERIES			
DRAWING TYPE		CUSTOMER		WWW.100Y.COM.TW			
SCALE		1:1	SHEET 1 OF 1				
DRAWING NO.		C-DS1015-04-XXXX-C					