


POLES	PART NO	DIMENSIONS(mm)	
		A	B
2	PHS-2Y	2.0	4.7
3	PHS-3Y	4.0	6.7
4	PHS-4Y	6.0	8.7
5	PHS-5Y	8.0	10.7
6	PHS-6Y	10.0	12.7
7	PHS-7Y	12.0	14.7
8	PHS-8Y	14.0	16.7
9	PHS-9Y	16.0	18.7
10	PHS-10Y	18.0	20.7
11	PHS-11Y	20.0	22.7
12	PHS-12Y	22.0	24.7
13	PHS-13Y	24.0	26.7
14	PHS-14Y	26.0	28.7
15	PHS-15Y	28.0	30.7
16	PHS-16Y	30.0	32.7



■ 技术参数 (SPECIFICATIONS)

- ◆ 额定电压: 100V AC DC
Voltage rating: 100V AC DC
- ◆ 额定电流: 1.0A AC DC MIN
Current rating: 1.0A AC DC MIN
- ◆ 耐压值: 800V AC/minute
Withstand voltage: 800V AC/minute
- ◆ 绝缘电阻: 500M Ω MIN
Insulation resistance: 500M Ω MIN
- ◆ 接触电阻: 0.02 Ω MAX
Contact resistance: 0.02 Ω MAX
- ◆ 工作温度: -25°C ~ +85°C
Working Temperature: -25°C ~ +85°C
- ◆ 间距: 2.0 mm
Pitch: 2.0 mm

■ 材料 (MATERIAL)

- ◆ 外壳: 尼龙66
Housing: PA66