



## ■ 技术参数 SPECIFICATIONS

- ◆ 适用线规: AWG#30~#22  
Applicable Wire: AWG#30~#22
- ◆ 额定电压: 125V DC,AC(rms)  
Rated voltage: 125V DC,AC(rms)
- ◆ 额定电流: 2A (AWG #22)  
Rated Current: 2A (AWG #22)
- ◆ 耐压值: 1000V AC/minute  
Withstand voltage: 1000V AC/min.
- ◆ 工作温度: -25°C ~ +85°C  
Working Temp : -25°C ~ +85°C
- ◆ 绝缘电阻: ≥1000 MΩ  
Insulation resistance: ≥1000 MΩ
- ◆ 接触电阻: ≤20mΩ  
Contact resistance: ≤20mΩ

## ■ 材料 MATERIAL

- ◆ 胶壳: 尼龙66, UL94-V0  
Housing: Nylon66, UL94-V0

|       | 2P  | 3P  | 4P   | 5P   | 6P   | 7P   | 8P   | 9P   | 10P  | 11P  | 12P  | 13P  | 14P  | 15P  | 16P  |
|-------|-----|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|
| DIM.A | 2.0 | 4.0 | 6.0  | 8.0  | 10.0 | 12.0 | 14.0 | 16.0 | 18.0 | 20.0 | 22.0 | 24.0 | 26.0 | 28.0 | 30.0 |
| DIM.B | 6.0 | 8.0 | 10.0 | 12.0 | 14.0 | 16.0 | 18.0 | 20.0 | 22.0 | 24.0 | 26.0 | 28.0 | 30.0 | 32.0 | 34.0 |