











RoHS
Compliant
2002/95/EC

REV.	ECN.	NO.	APPD.



RECOMMENDED PCB LAYOUT



NOTES:

- ELECTRICAL CHARACTERISTIC:
 - VOLTAGE CURRENT RATING: 1AMP, 30VAC;
 - INSULATION RESISTANCE: 1000MΩ, MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
- Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
- NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.

4. PART, NO.

USAF-08*N-1*P62

1: Au 1U"
6: Au 30U"

W: WHITE
B: BLACK

1: PBT
2: PA6T
3: PA9T
4: LCP

Bill of materials:

3	HOUSING	PBT/LCP+30%GF, UL94 V-0	1	UL 94V-0	X. ±0.35	X.* ±2°	UNITS mm					
2	SHELL	COPPER ALLOY & SPCC-SD	1	PLATED Ni	.X ±0.3	.X.* ±1°	MAT'L					
1	TERMINAL	COPPER ALLOY	4	GOLD/TIN PLATED	.XX ±0.25	.XX*	SEE NOTE	TITLE:		PART NO.:		
					.XXX ±0.15	.XXX*	FINISH	USB A F DIP 180° 双层短体		USAF-08*N-1*P62		
NO	PARTS	MATERIAL	QTY	FINISHING	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC.		SEE NOTE	DR:	Sandy 2009/8/17		DWG NO.:	
							Q'TY	CHKD:	Sandy 2009/8/18		AII-P62	
								APPD:			SCALE	SHEET