

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



## 284-621

**Distribution terminal block 3 x CAGE CLAMP® connection 10 mm<sup>2</sup> 1 x screw-clamp connection 35 mm<sup>2</sup>/AWG 2**

Packing unit 15 pieces

**RoHS compliant**

Product group 1 (Rail Mounted Terminal Blocks)

Cross section [mm<sup>2</sup>] 0.2 - 10 mm<sup>2</sup>

Cross section [AWG] 24 - 8 AWG

Connection method CAGE CLAMP®CONNECTION

Number of strands 73

Cross section [mm<sup>2</sup>] 6 - 35 mm<sup>2</sup>

Cross section [AWG] 10 - 2 AWG

Measured voltage EN 800 V

Measured shock voltage 8 kV

Pollution degree 3

Current intensity EN 125 A

Weight 55.5 g

Color grey

Wiring type Front-/Side-entry

No. of connection Points 4

No. of potentials 1

Height 39.5 mm

Height 1.55 in

Width	17.5 mm
Width	0.689 in
Depth	89 mm
Depth	3.507 in
Strip length from	12 mm
Strip length to	14 mm
Strip length	0.51 in
Safety information 1	Screw torque: 3.5 Nm
Mounting	TS 35
Connection type	cage clamp® / screw clamp connection

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)