

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



750-344

INTERBUS ECO fieldbus coupler 500 kBaud digital and analog signals

Packing unit 1 piece

Product group	15 (Remote I/O)
Max. no. of nodes	256
Max. no. Of I/O points	4096 (depends on Master)
Transmission medium	certified Cu cable
Max. length of fieldbus segment	400 m
Data transmission rate (kBaud)	500 kBaud
Buscoupler connection	1 x D-SUB 9; plug for input interface 1 x D-SUB 9; socket for output interface
Conformity marking	CE
Max. no. of I/O modules	64
Configuration	via PC or PLC
Voltage supply	DC 24 V (-15% / + 20%)
Input current (max)	260 mA
Efficiency of the power supply	80 %
Internal current consumption	350 mA
Total current for the I/O modules	650 mA
Operating temperature	0 °C ... + 55 °C
Storage temperature	-25 °C ... +85 °C
Relative air humidity	95 %
Vibration resistance	acc. IEC 60068-2-6
Shock resistance	acc. IEC 60068-2-27

Degree of protection	IP 20
Approvals	ATEX
Cross section [mm ²]	0.08 - 1.5 mm ²
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP®CONNECTION
Weight	115 g
Color	light grey
Height	65 mm
Height	2.56 in
Width	50 mm
Width	1.969 in
Depth	97 mm
Depth	3.819 in
Strip length from	5 mm
Strip length to	6 mm
Strip length	0.22 in
Manuals	available as download on the Internet under "www.wago.com/Service/Download" or on the CD "ELECTRONICC Tools and Docs" (Item No.: 0888-0412/0001-0101)
Customs Tariff No.	85176200
Country of Origin	Deutschland
Mounting	TS 35

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)