

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



## 769-606/005-000

**Plug With CAGE CLAMP®connection and snap-in flanges for mounting without tools pin spacing 5 mm /  
 0.197 in 6 pole**

Packing unit 25 pieces

**RoHS compliant**

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 6

Cross section [mm<sup>2</sup>] 0.08 - 4 mm<sup>2</sup>

Cross section [AWG] 28 - 12 AWG

Connection method CAGE CLAMP®CONNECTION

Measured voltage EN 500 V

Measured shock voltage 6 kV

Pollution degree 3

Current intensity EN 32 A

Weight 19.677 g

Color grey

Wiring type Front-entry

No. of connection Points 6

No. of potentials 6

Height 24.4 mm

Height 0.961 in

Width	51.3 mm
Width	2.02 in
Depth	40.8 mm
Depth	1.606 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)