

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-609/001-000

Plug with CAGE CLAMP®connection and snap-in mounting feet with mounting feet 209-137 on ts 35 3.5 mmø for sheet thickness 0.6-1.2 mm pin spacing 5 mm / 0.197 in 9 pole

Packing unit 25 pieces

RoHS compliant

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 9

Cross section [mm²] 0.08 - 4 mm²

Cross section [AWG] 28 - 12 AWG

Connection method CAGE CLAMP®CONNECTION

Measured voltage EN 500 V

Measured shock voltage 6 kV

Pollution degree 3

Current intensity EN 32 A

Weight 26.458 g

Color grey

Wiring type Front-entry

No. of connection Points 9

No. of potentials 9

Height 18.3 mm

Height 0.72 in

Width	48.6 mm
Width	1.913 in
Depth	40.2 mm
Depth	1.583 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)