

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-610/004-000

Plug with CAGE CLAMP®connection and fixing flanges for screw or similar mounting types for parallel or perpendicular mounting pin spacing 5 mm / 0.197 in 10 pole

Packing unit 25 pieces

RoHS compliant

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 10

Cross section [mm²] 0.08 - 4 mm²

Cross section [AWG] 28 - 12 AWG

Measured voltage EN 500 V

Measured shock voltage 6 kV

Pollution degree 3

Current intensity EN 32 A

Weight 30.433 g

Color grey

Wiring type Front-entry

No. of connection Points 10

No. of potentials 10

Height 18.3 mm

Height 0.72 in

Width 64.7 mm

Width	2.547 in
Depth	40.2 mm
Depth	1.583 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)