

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-611/001-000

**Plug with CAGE CLAMP®connection and snap-in mounting feet for sheet thickness 0.6-1.2 mm 3.5 mmø
 with mounting feet 209-137 on ts 35 pin spacing 5 mm / 0.197 in 11 pole**

Packing unit 25 pieces

RoHS compliant

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 11

Cross section [mm²] 0.08 - 4 mm²

Cross section [AWG] 28 - 12 AWG

Connection method CAGE CLAMP®CONNECTION

Measured voltage EN 500 V

Measured shock voltage 6 kV

Pollution degree 3

Current intensity EN 32 A

Weight 32.124 g

Color grey

Wiring type Front-entry

No. of connection Points 11

No. of potentials 11

Height 18.3 mm

Height 0.72 in

Width	58.6 mm
Width	2.307 in
Depth	40.2 mm
Depth	1.583 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)