

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-614/001-000

**Plug with CAGE CLAMP®connection and snap-in mounting feet for sheet thickness 0.6-1.2 mm 3.5 mmø
 with mounting feet 209-137 on ts 35 pin spacing 5 mm / 0.197 in 14 pole**

Packing unit 15 pieces

RoHS compliant

Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	14
Cross section [mm²]	0.08 - 4 mm²
Cross section [AWG]	28 - 12 AWG
Connection method	CAGE CLAMP®CONNECTION
Measured voltage EN	500 V
Measured shock voltage	6 kV
Pollution degree	3
Current intensity EN	32 A
Weight	40.728 g
Color	grey
Wiring type	Front-entry
No. of connection Points	14
No. of potentials	14
Height	18.3 mm
Height	0.72 in

Width	73.6 mm
Width	2.898 in
Depth	40.2 mm
Depth	1.583 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-8-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)