

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-641

Plug with straight solder pin mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 11 pole

Packing unit 25 pieces

RoHS compliant

Measured shock voltage	4 kV
Weight	11.053 g
Measured voltage EN	500 V
Pollution degree	2
Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	11
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Color	grey
Wiring type	Front-entry
No. of connection Points	11
No. of potentials	11
Height	22.2 mm
Height	0.874 in

Width	58.6 mm
Width	2.307 in
Depth	18.3 mm
Depth	0.72 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)