

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-644

Plug with straight solder pin mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 14 pole

Packing unit 25 pieces

RoHS compliant

Measured shock voltage	4 kV
Measured voltage EN	500 V
Pollution degree	2
Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	14
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Weight	14.032 g
Color	grey
Wiring type	Front-entry
No. of connection Points	14
No. of potentials	14
Height	22.2 mm
Height	0.874 in

Width	73.6 mm
Width	2.898 in
Depth	18.3 mm
Depth	0.72 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)