

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-645/003-000

Plug mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 15 pole	
Packing unit 15 pieces	
RoHS compliant	
Measured shock voltage	4 kV
Strip length from	10 mm
Measured voltage EN	500 V
Pollution degree	2
No. of connection Points	15
No. of potentials	15
Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	15
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Weight	15.69 g
Color	grey
Wiring type	Front-entry
Height	18.3 mm

Height	0.72 in
Width	89.7 mm
Width	3.531 in
Depth	22.2 mm
Depth	0.874 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)