

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



## 769-662

Plug with right angled solder pin mating direction parallel to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 2 pole

Packing unit 200 pieces

**RoHS compliant**

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 2

Measured voltage EN 250 V

Measured shock voltage 4 kV

Pollution degree 3

Current intensity EN 32 A

Measured voltage EN 500 V

Measured shock voltage 4 kV

Pollution degree 2

Weight 2.567 g

Color grey

Wiring type Front-entry

No. of connection Points 2

No. of potentials 2

Height 18.3 mm

Height 0.72 in

Width	11.2 mm
Width	0.441 in
Depth	22.2 mm
Depth	0.874 in

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)