


勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



## 769-669/004-00

<b>Plug mating direction parallel to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 9 pole</b>	
Packing unit 25 pieces	
<b>RoHS compliant</b>	
Measured shock voltage	4 kV
Strip length from	5 mm
Measured voltage EN	500 V
Pollution degree	2
Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	9
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Weight	10.987 g
Color	grey
Wiring type	Front-entry
No. of connection Points	9
No. of potentials	9
Height	18.3 mm
Height	0.72 in

Width	59.7 mm
Width	2.35 in
Depth	22.2 mm
Depth	0.874 in

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)