

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-675/003-000

Plug mating direction parallel to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 15 pole	
Packing unit 15 pieces	
RoHS compliant	
Measured shock voltage	4 kV
Strip length from	10 mm
Measured voltage EN	500 V
Pollution degree	2
Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	15
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Weight	16.74 g
Color	grey
Wiring type	Front-entry
No. of connection Points	15
No. of potentials	15
Height	18.3 mm
Height	0.72 in

Width	89.7 mm
Width	3.531 in
Depth	22.2 mm
Depth	0.874 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)