

## 電子線

型號	溫度	電壓	導體尺寸	絕緣	
				Insulation	
UL Style No.	Temp Rating	Voltage Rating	Cond. Size <sup>1</sup>	Thick. <sup>9</sup>	Material. <sup>2</sup>
	°C	V	AWG	mm	-
1007	80	300 <sup>7</sup>	32-16	0.4	PVC
1011	80	600 <sup>8</sup>	28-10	0.8	PVC
1013	90	600 <sup>8</sup>	28-10	0.8	PVC
1015	105	600 <sup>8</sup>	28-10	0.8	PVC
1028	105	600 <sup>8</sup>	22-10	1.2	PVC
1032	90	1000	26-10	0.8	PVC
1061	80	300	30-16	0.25	SR-PVC
1095	80	300	30-16	0.3	PVC
1195	80	300	30-14	0.4	PVC, SR-PVC
1208	80	300	30-16	0.4	PVC, SR-PVC
1429	80	150 <sup>6</sup>	32-16	0.25	XL-PCV
1430	105	300 <sup>7</sup>	30-16	0.4	XL-PCV
1431	105	600 <sup>8</sup>	28-10	Variable <sup>5</sup>	XL-PCV
1472	80	125 <sup>6</sup>	30-20	0.2	XL-PCV
1534	80	N.S. <sup>3</sup>	30-14	0.3	XL-PCV
1536	80	N.S. <sup>3</sup>	30-10	0.3	XL-PCV