


YK-211 PITCH-6.35mm




Materials Electrical

Rated: 250V 10A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40°C~+105°C
 Screw Torque Value: 6.1 Lb-In.
 Suitable Electric Wire: 22-18AWG
 1) Molded Parts: Thermoplastic UL94V-0 Black
 2) Terminal: Brass 0.8t Tin Plated
 3) Terminal Screw: Steel M3 Ni Plated
 Approval:

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A	13.70	20.05	26.40	32.75	39.10	45.45	51.80	58.15	64.50	70.85	77.20	83.55	89.90	96.25	102.60	108.95	115.30	121.65	128.00	134.35	140.70	147.05	153.40	159.75	166.10	172.45	178.80	185.15	191.45
B	6.35	12.70	19.05	25.40	31.75	38.10	44.45	50.80	57.15	63.50	69.85	76.20	82.55	88.90	95.25	101.60	107.95	114.30	120.65	127.00	133.35	139.70	146.05	152.40	158.75	165.10	171.45	177.80	184.15

YK-311 PITCH-7.62mm




Materials Electrical

Rated: 250V 15A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40°C~+105°C
 Screw Torque Value: 5.3 Lb-In.
 Suitable Electric Wire: 22-16AWG
 1) Molded Parts: Thermoplastic UL94V-0 Black
 2) Terminal: Brass 0.8t Tin Plated
 3) Terminal Screw: Steel M3 Ni Plated
 Approval:

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A	16.74	24.36	31.98	39.60	47.22	54.84	62.46	70.08	77.70	85.32	92.94	100.56	108.18	115.80	123.42	131.04	138.66	146.28	153.90	161.52	169.14	176.76	184.38	192.00	199.62	207.24	214.86	222.48	230.10
B	7.62	15.24	22.86	30.48	38.10	45.72	53.34	60.96	68.58	76.20	83.82	91.44	99.06	106.68	114.30	121.92	129.54	137.16	144.78	152.40	160.02	167.64	175.26	182.88	190.50	198.12	205.74	213.36	220.98


YK-312 PITCH-7.62mm



Materials Electrical

Rated: 250V 15A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40°C~+105°C
 Screw Torque Value: 5.3 Lb-In.
 Suitable Electric Wire: 22-16AWG
 1) Molded Parts: Thermoplastic UL94V-0 Black
 2) Terminal: Brass 0.8t Tin Plated
 3) Terminal Screw: Steel M3 Ni Plated
 Approval:


YK-313 PITCH-7.62mm



Materials Electrical

Rated: 250V 15A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40°C~+105°C
 Screw Torque Value: 5.3 Lb-In.
 Suitable Electric Wire: 22-16AWG
 1) Molded Parts: Thermoplastic UL94V-0 Black
 2) Terminal: Brass 0.8t Tin Plated
 3) Terminal Screw: Steel M3 Ni Plated
 Approval:

YK-314 PITCH-7.62mm



Materials Electrical

Rated: 250V 15A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40°C~+105°C
 Screw Torque Value: 5.3 Lb-In.
 Suitable Electric Wire: 22-16AWG
 1) Molded Parts: Thermoplastic UL94V-0 Black
 2) Terminal: Brass 0.8t Tin Plated
 3) Terminal Screw: Steel M3 Ni Plated
 Approval:

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)