


**Materials Electrical**  
 Rated: 300V 20A  
 Insulation Withstands Voltage: AC2000V/min  
 Insulation Resistance: 1000MΩ or More at DC500V  
 Using Temperature Range: -40C~+105C  
 Screw Torque Value: 8.8 Lb-In.  
 Suitable Electric Wire: 22-12AWG  
 1)Molded Parts: Thermoplastic UL94V-0 Black  
 2)Terminal: Brass 0.8t Tin Plated  
 3)Terminal Screw: Steel M3 Ni Plated  
 Approval:

**Materials Electrical**  
 Rated: 300V 20A  
 Insulation Withstands Voltage: AC2000V/min  
 Insulation Resistance: 1000MΩ or More at DC500V  
 Using Temperature Range: -40C~+105C  
 Screw Torque Value: 8.8 Lb-In.  
 Suitable Electric Wire: 22-12AWG  
 1)Molded Parts: Thermoplastic UL94V-0 Black  
 2)Terminal: Brass 0.8t Tin Plated  
 3)Terminal Screw: Steel M3 Ni Plated  
 Approval:

**Materials Electrical**  
 Rated: 300V 20A  
 Insulation Withstands Voltage: AC2000V/min  
 Insulation Resistance: 1000MΩ or More at DC500V  
 Using Temperature Range: -40C~+105C  
 Screw Torque Value: 8.8 Lb-In.  
 Suitable Electric Wire: 22-12AWG  
 1)Molded Parts: Thermoplastic UL94V-0 Black  
 2)Terminal: Brass 0.8t Tin Plated  
 3)Terminal Screw: Steel M3 Ni Plated  
 Approval:

**Materials Electrical**  
 Rated: 300V 20A  
 Insulation Withstands Voltage: AC2000V/min  
 Insulation Resistance: 1000MΩ or More at DC500V  
 Using Temperature Range: -40C~+105C  
 Screw Torque Value: 8.8 Lb-In.  
 Suitable Electric Wire: 22-12AWG  
 1)Molded Parts: Thermoplastic UL94V-0 Black  
 2)Terminal: Brass 0.8t Tin Plated  
 3)Terminal Screw: Steel M3 Ni Plated  
 Approval:

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
A	19.00	27.25	35.50	43.75	52.00	60.25	68.50	76.75	85.00	93.25	101.50	109.75	118.00	126.25	134.50	142.75	151.00	159.25	167.50
B	8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75	132.00	140.25	148.50	156.75



**Materials Electrical**  
 Rated: 300V 20A  
 Insulation Withstands Voltage: AC2000V/min  
 Insulation Resistance: 1000MΩ or More at DC500V  
 Using Temperature Range: -40C~+105C  
 Screw Torque Value: 8.8 Lb-In.  
 Suitable Electric Wire: 22-12AWG  
 1)Molded Parts: Thermoplastic UL94V-0 Black  
 2)Terminal: Brass 0.8t Tin Plated  
 3)Terminal Screw: Steel M3 Ni Plated  
 Approval:

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
A	19.00	27.25	35.50	43.75	52.00	60.25	68.50	76.75	85.00	93.25	101.50	109.75	118.00	126.25	134.50	142.75	151.00	159.25	167.50
B	8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75	132.00	140.25	148.50	156.75

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)