


Materials Electrical
 Rated: 300V 20A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40℃~+105℃
 Screw Torque Value: 8.8 Lb-In.
 Suitable Electric Wire: 22~12AWG
 1)Molded Parts: Thermoplastic UL94V-0 Black
 2)Terminal: Brass 0.8t Tin Plated
 3)Terminal Screw: Steel M3 Ni Plated
 Approval:

Materials Electrical
 Rated: 300V 20A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40℃~+105℃
 Screw Torque Value: 8.8 Lb-In.
 Suitable Electric Wire: 22~12AWG
 1)Molded Parts: Thermoplastic UL94V-0 Black
 2)Terminal: Brass 0.8t Tin Plated
 3)Terminal Screw: Steel M3 Ni Plated
 Approval:

Materials Electrical
 Rated: 300V 20A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40℃~+105℃
 Screw Torque Value: 8.8 Lb-In.
 Suitable Electric Wire: 22~12AWG
 1)Molded Parts: Thermoplastic UL94V-0 Black
 2)Terminal: Brass 0.8t Tin Plated
 3)Terminal Screw: Steel M3 Ni Plated
 Approval:

Materials Electrical
 Rated: 300V 20A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40℃~+105℃
 Screw Torque Value: 8.8 Lb-In.
 Suitable Electric Wire: 22~12AWG
 1)Molded Parts: Thermoplastic UL94V-0 Black
 2)Terminal: Brass 0.8t Tin Plated
 3)Terminal Screw: Steel M3 Ni Plated
 Approval:

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A	18.50	26.75	35.00	43.25	51.50	59.75	68.00	76.25	84.50	92.75	101.00	109.25	117.50	125.75	134.00	142.25	150.50	158.75	167.00	175.25	183.50	191.75	200.00	208.25	216.50	224.75	233.00	241.25	249.50
B	8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75	132.00	140.25	148.50	156.75	165.00	173.25	181.50	189.75	198.00	206.25	214.50	222.75	231.00	239.25



Materials Electrical
 Rated: 300V 20A
 Insulation Withstands Voltage: AC2000V/min
 Insulation Resistance: 1000MΩ or More at DC500V
 Using Temperature Range: -40℃~+105℃
 Screw Torque Value: 8.8 Lb-In.
 Suitable Electric Wire: 22~12AWG
 1)Molded Parts: Thermoplastic UL94V-0 Black
 2)Terminal: Brass 0.8t Tin Plated
 3)Terminal Screw: Steel M3 Ni Plated
 Approval:

POLE	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
A	18.50	26.75	35.00	43.25	51.50	59.75	68.00	76.25	84.50	92.75	101.00	109.25	117.50	125.75	134.00	142.25	150.50	158.75	167.00	175.25	183.50	191.75	200.00	208.25	216.50	224.75	233.00	241.25	249.50
B	8.25	16.50	24.75	33.00	41.25	49.50	57.75	66.00	74.25	82.50	90.75	99.00	107.25	115.50	123.75	132.00	140.25	148.50	156.75	165.00	173.25	181.50	189.75	198.00	206.25	214.50	222.75	231.00	239.25

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)