

圖號 DRAWING No. :FP3BT-V-0		校訂版次 REVISIONS			
品名 NAME:Blade	ITEM No. :	版次	記述 DESCRIPTION	DATE	核可

NOTE:

1. MAXIMUM ELECTRICAL RATING:75°C 600 VOLTS
2. WIRE RANGE:22-16 AWG / 0.5-1.5 mm²
INSULATED COLOR:RED
3. WIRE RANGE:16-14 AWG / 1.5-2.5 mm²
INSULATED COLOR:BLUE
4. WIRE RANGE:12-10 AWG / 4-6 mm²
INSULATED COLOR:YELLOW
5. MATERIAL THICKNESS:t
TOLERANCE:±0.05

MAXIMUM ELECTRIC CURRENT								
A. W. G	22	20	18	16	14	12	10	
MAX AMP	9	12	17	18	30	35	50	

WIRE RANGE AWG/mm ²	產品編號 ITEM NO.	B ±0.20	F ±0.40	L ±1.00	E ±0.60	D ±0.80	d1 ±0.20	t
22-16 AWG 0.5-1.5 mm ²	BT1-10V	2.4	10.7	20.7	10.0	4.1	1.7	0.75
	BT1-11V	3.0	11.0	21.0				
	BT1-14V	3.0	14.0	24.0				
	BT1-18V	2.4	18.0	28.0				
16-14 AWG 1.5-2.5 mm ²	BT2-9V	2.8	9.0	19.0	10.0	4.5	2.3	0.8
	BT2-10V	2.4	10.7	20.7				
	BT2-13V	2.4	13.0	23.0				
	BT2-18V	2.4	18.0	28.0				
12-10 AWG 4-6 mm ²	BT5-10V	2.8	10.0	22.5	12.5	6.5	3.4	1.0
	BT5-14LV	4.5	14.0	26.5				
	BT5-18V	3.0	18.0	30.5				

認可 APPROVALS	第三視角 THIRD VIEW	MATERIAL	單位UNIT
製圖 DRAFT:		INSULATION:VINYL	m/m
設計 DESIGN:		MATERIAL:COPPER	比例SCALE
核可 CHECKED:		TIN PLATING	

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)