



























NON-INSULATED CORD-END TERMINALS(DIN 46228/4)

Feature:

- 1.TEMPERATURE RANGE:--40°C UP TO+105°C
- 2.TERMINAL MATERIAL:COPPER TUBE
3. PLATING:ELECTRO TIN PLATED
- 4.INSULATED MATERIAL:NYLON

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Specification:

WIRE RANGE mm ²	ITEM NO.	DIMENSIONS inch (mm)				COLOR SYSTEM			PACKING PCS
		F	L	C	W	FRENCH	GERMAN	DIN	
0.14	CE001406	.236 (6.0)	.394 (10.0)	.028 (.70)	.063 (1.6)		 GREY		1000 PCS
	CE001408	.315 (8.0)	.472 (12.0)						
0.25	CE002506	.236 (6.0)	.394 (10.0)	.030 (.75)	.075 (1.9)	 VIOLET	 LIGHT BLUE		
	CE002508	.315 (8.0)	.472 (12.0)						
0.34	CE003406	.236 (6.0)	.394 (10.0)	.031 (.80)		 PINK	 TURQUOISE		
	CE003408	.315 (8.0)	.472 (12.0)						
0.5	CE005006	.236 (6.0)	.472 (12.0)	.039 (1.0)	.102 (2.6)	 WHITE	 ORANGE	 WHITE	
	CE005008	.315 (8.0)	.551 (14.0)						
	CE005010	.394 (10.0)	.630 (16.0)						
0.75	CE007506	.236 (6.0)	.472 (12.0)	.047 (1.2)	.110 (2.8)	 BLUE	 WHITE	 GREY	
	CE007508	.315 (8.0)	.551 (14.0)						
	CE007510	.394 (10.0)	.630 (16.0)						
	CE007512	.472 (12.0)	.709 (18.0)						
1.0	CE010006	.236 (6.0)	.472 (12.0)	.055 (1.4)	.118 (3.0)	 RED	 YELLOW	 RED	
	CE010008	.315 (8.0)	.551 (14.0)						
	CE010010	.394 (10.0)	.630 (16.0)						
	CE010012	.472 (12.0)	.709 (18.0)						
1.5	CE015008	.315 (8.0)	.551 (14.0)	.067 (1.7)	.138 (3.5)	 BLACK	 RED	 BLACK	
	CE015010	.394 (10.0)	.630 (16.0)						
	CE015012	.472 (12.0)	.709 (18.0)						
	CE015018	.709 (18.0)	.945 (24.0)						
2.5	CE025008	.315 (8.0)	.551 (14.0)	.087 (2.2)	.165 (4.2)	 GREY	 BLUE	 BLUE	
	CE025010	.394 (10.0)	.630 (16.0)						
	CE025012	.472 (12.0)	.709 (18.0)						
	CE025018	.709 (18.0)	.945 (24.0)						
4.0	CE040010	.394 (10.0)	.669 (17.0)	.110 (2.8)	.189 (4.8)	 ORANGE	 GREY	 GREY	
	CE040012	.472 (12.0)	.787 (20.0)						
	CE040018	.709 (18.0)	1.024 (26.0)						
6.0	CE060012	.472 (12.0)	.787 (20.0)	.138 (3.5)	.248 (6.3)	 GREEN	 BLACK	 YELLOW	
	CE060018	.709 (18.0)	1.024 (26.0)						
10	CE100012	.472 (12.0)	.866 (22.0)	.177 (4.5)	.299 (7.6)	 BROWN	 IVORY	 RED	
	CE100018	.709 (18.0)	1.102 (28.0)						
16	CE160012	.472 (12.0)	.945 (24.0)	.228 (5.8)	.346 (8.8)	 IVORY	 GREEN	 BLUE	
	CE160018	.709 (18.0)	1.102 (28.0)						
25	CE250016	.630 (16.0)	1.181 (30.0)	.287 (7.3)	.441 (11.2)	 BLACK	 BROWN	 YELLOW	
	CE250022	.866 (22.0)	1.417 (36.0)						
35	CE350016	.630 (16.0)	1.181 (30.0)	.327 (8.3)	.500 (12.7)	 RED	 BEIGE	 RED	
	CE350018	.709 (18.0)	1.260 (32.0)						
	CE350025	.984 (25.0)	1.535 (39.0)						
50	CE500020	.787 (20.0)	1.417 (36.0)	.406 (10.3)	.591 (15.0)	 BLUE	 OLIVE	 BLUE	
	CE500025	.984 (25.0)	1.575 (40.0)						
70	CE700021	.827 (21.0)	1.457 (37.0)	.531 (13.5)	.630 (16.0)	 YELLOW	 YELLOW	 YELLOW	
95	CE950025	.984 (25.0)	1.732 (44.0)	.579 (14.7)	.709 (18.0)	 RED	 RED	 RED	
120	CE120027	1.063 (27.0)	1.890 (48.0)	.657 (16.7)	.787 (20.0)	 BLUE	 BLUE	 BLUE	
150	CE150032	1.260 (32.0)	2.283 (58.0)	.768 (19.5)	.906 (23.0)	 YELLOW	 YELLOW	 YELLOW	

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)