

# CL4262 纯铜大电流 32A/1KV 全绝缘鳄鱼夹需插 4mm 香蕉插头连接 Alliga

颜色分类

红色

黑色

黄色

绿色

蓝色

白色

<i>P/N: CL4262 *color Insulated Large Safety Alligator Clip Made of Brass With 4mm Socket</i>	
材质 (Material)	PA 尼龙+黄铜镀镍 (PA Nylon housing +Nickel Plated brass)
电流电压(Rating)	CATIII 1000Vac/32A max. ,IEC61010 Compliant
工作温度(Working Temp.)	-20 ℃ ~+80℃
颜色 (Color)	红-黑-黄-绿-蓝 (Red-Black-Yellow-Green-Blue-White)
连接方式(Connection )	标准4mm香蕉插座, 可插护套-非护套-伸缩护套香蕉插头 (Compatible with all Shrouded-Unshrouded-Retractable spring-loaded 4mm banana plugs)
重量(Weight)/包装(P'KG)	14.6 g/pc -50pcs/Polybag
外形尺寸(Drawing)	长度(Length):83.5mm, 最大张口(Jaw Open):27mm 

2.底部符合CATIII 1000V欧盟CE标记



鳄鱼夹头部最小宽度尺寸**5.81mm**

鳄鱼夹嘴部最小宽度



**3.此鳄鱼夹不能直接焊线使用,需要把导线焊接到4mm香蕉插头上(需另购-护套,非护套,伸缩护套插头都可以),香蕉插头直接插到此鳄鱼夹尾部,方便快速连接。**

A. 高压使用场合应优先采用护套型4mm 安全香蕉插头, 确保插头和鳄鱼夹连接处双重绝缘:

B. 低压使用场合可选用普通标准4mm香蕉插头

胜特力材料 886-3-5773766  
 胜特力电子(上海) 86-21-34970699  
 胜特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Application Example:



推荐使用香蕉插头(Recommend 4mm Plugs):



推荐连接测试线(Recommend Test Leads):



效果图(Test leads kit):

P/N: TL22202

P/N: TL22202

