







































**TWIN CORD-END TERMINALS(DIN 46228/4)**

**Feature:**

- 1.TEMPERATURE RANGE:-40°C UP TO+105°C
- 2.TERMINAL MATERIAL:COPPER TUBE
3. PLATING:ELECTRO TIN PLATED
- 4.INSULATED MATERIAL:NYLON

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Specification:

| WIRE RANGE<br>mm <sup>2</sup> | ITEM NO. | DIMENSIONS inch (mm) |              |             |             |            | COLOR SYSTEM  |  |  | PACKING<br>PCS |
|-------------------------------|----------|----------------------|--------------|-------------|-------------|------------|---|--|--|----------------|
|                               |          | F                    | L            | C           | W1          | W2         | FRENCH  | GERMAN   | DIN  |                |
| 2 x 0.5                       | CT205008 | .315 (8.0)           | .591 (15.0)  | .059 (1.5)  | .185 (4.7)  | .098 (2.5) |  WHITE  |  ORANGE |  WHITE  | 500 PCS        |
| 2 x 0.75                      | CT207508 | .315 (8.0)           | .591 (15.0)  | .071 (1.8)  | .197 (5.0)  | .110 (2.8) |  BLUE   |  WHITE  |  GREY   |                |
|                               | CT207510 | .394 (10.0)          | .669 (17.0)  |             |             |            |  RED    |  YELLOW |  RED    |                |
| 2 x 1.0                       | CT210008 | .315 (8.0)           | .591 (15.0)  | .081 (2.05) | .213 (5.4)  | .134 (3.4) |  BLACK  |  RED    |  BLACK  |                |
|                               | CT210010 | .394 (10.0)          | .669 (17.0)  |             |             |            |  GREY   |  BLUE   |  BLUE   |                |
| 2 x 1.5                       | CT215008 | .315 (8.0)           | .630 (16.0)  | .091 (2.3)  | .260 (6.6)  | .142 (3.6) |  ORANGE |  GREY   |  GREY   |                |
|                               | CT215012 | .472 (12.0)          | .787 (20.0)  |             |             |            |  GREEN  |  BLACK  |  YELLOW |                |
| 2 x 2.5                       | CT225010 | .394 (10.0)          | .728 (18.5)  | .110 (2.8)  | .307 (7.8)  | .165 (4.2) |  BROWN  |  IVORY  |  RED    |                |
|                               | CT225013 | .512 (13.0)          | .846 (21.5)  |             |             |            |  IVORY  |  GREEN  |  BLUE   |                |
| 2 x 4.0                       | CT240012 | .472 (12.0)          | .906 (23.0)  | .146 (3.7)  | .346 (8.8)  | .193 (4.9) |  GREEN  |  BLACK  |  YELLOW |                |
| 2 x 6.0                       | CT260014 | .551 (14.0)          | 1.024 (26.0) | .189 (4.8)  | .394 (10.0) | .272 (6.9) |  RED    |  IVORY  |  RED    |                |
| 2 x 10.0                      | CT210014 | .551 (14.0)          | 1.043 (26.5) | .252 (6.4)  | .504 (12.8) | .299 (7.6) |  IVORY  |  GREEN  |  BLUE   |                |
| 2 x 16.0                      | CT216014 | .551 (14.0)          | 1.240 (31.5) | .327 (8.3)  | .732 (18.6) | .378 (9.6) |  IVORY  |  GREEN  |  BLUE   |                |

勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-54151736

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)