



TEST LEADS & ACCESSORIES

KHG-4 / KHN-4




- The 4mm stackable safety plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold/Nickel-plated
- Rated current : 50V 19A

KAG-4 / KAN-4




- The 4mm stackable plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold/Nickel-plated
- Rated current : 50V 19A

KBG-4 / KBN-4




- The 4mm plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold/Nickel-plated
- Rated current : 50V 19A

KAG-2




- The 2mm plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold-plated
- Rated current : 50V 10A

KBG-2




- The 2mm plug is machined from brass with movable multilam contact cage spring
- Contact surface : Gold-plated
- Rated current : 50V 10A

KDN-42 / KDN-44




- Adaptors for interconnecting between 2mm and 4mm system
- 4mm plug to 2mm socket
- 4mm plug to 4mm socket
- Contact surface : Nickel-plated
- Rated : 50V 19A

KBL-2




- Bezel to suit 2mm socket for identification purpose
- Suited for KSG-30A
- Panel mounting hole : 4.2mm

KBL-4




- Bezel to suit 4mm socket for identification purpose
- Suited for KSG-50A
- Panel mounting hole : 6.2mm

KCG-210




- The 2mm connecting plug suitable for general interconnection on 2mm socket
- Contact surface : Gold-plated
- Rated : 50V 10A
- Spacing : 10mm
- Color : Black

KCN-419




- The 4mm connecting plug suitable for general interconnection on 4mm socket
- Contact surface : Nickel-plated
- Rated : 50V 19A
- Spacing : 19mm
- Color : Black

KCN-419A




- The safety 4mm connecting plug suitable for general interconnection on 4mm safety socket
- Contact surface : Nickel-plated
- Rated : 50V 19A
- Spacing : 19mm
- Color : Black

KCN-419B




- The safety 4mm connecting plug with two 4mm in-line safety socket suitable for general interconnection on 4mm safety socket
- Contact surface : Nickel-plated
- Rated : 50V 19A
- Spacing : 19mm
- Color : Black

KEG-4 / KEN-4




- A range of shrouded 4mm sockets offered for soldering or 6.4mm fast termination
- Panel mounting hole : 12 x 11mm
- Contact surface : Gold/Tin-plated
- Rated : 50V 19A

KFG-4 / KFN-4




- A range of shrouded 4mm sockets offered for soldering or 6.4mm fast termination
- Panel mounting hole : 12.4mm
- Contact surface : Gold/Tin-plated
- Rated : 50V 19A

KPG-4 / KPN-4














- A range of shrouded 4mm sockets offered for soldering or 6.4mm fast termination
- Panel mounting hole : 7.8 x 7mm
- Contact surface : Gold/Tin-plated

KPG-2



- 2mm panel-mounting round socket with brass insert accepts a wide range 2mm plugs
- Panel mounting hole : 5.6 x 5mm
- Contact surface : Gold-plated
- Rated : 50V 10A

<p>KWG-4 / KWN-4</p>  <ul style="list-style-type: none"> • 4mm stackable safety plug with cage springs • Contact surface : Gold/ Nickel-plated • Rated : 50V 19A • Length : 25.50.75.100cm 	<p>KLG-4 / KLN-4</p>  <ul style="list-style-type: none"> • 4mm stackable plug with cage springs • Contact surface : Gold/Nickel-plated • Rated : 50V 19A • Length : 25.50.75.100cm 	<p>KMG-4 / KMN-4</p>  <ul style="list-style-type: none"> • 4mm plug with cage springs • Contact surface : Gold/Nickel-plated • Rated : 50V 19A • Length : 25.50.75.100cm 	<p>KLG-2</p>  <ul style="list-style-type: none"> • 2mm stackable plug with cage springs • Contact surface : Gold-plated • Rated : 50V 10A • Length : 15.30.45.60cm
<p>Color : Black, Red, Yellow, Blue, White, Green</p>	<p>Color : Black, Red, Yellow, Blue, White, Green</p>	<p>Color : Black, Red, Yellow, Blue, White, Green</p>	<p>Color : Black, Red, Yellow, Blue, White, Green</p>
<p>KMG-2</p>  <ul style="list-style-type: none"> • 2mm plug with cage springs • Contact surface : Gold-plated • Rated : 50V 10A • Length : 15.30.45.60mm 	<p>KLG-0.5</p>  <ul style="list-style-type: none"> • 0.5mm plug is machined from phosphor bronze. • 2.5Φ Test-Ring in parallel • Contact surface : Gold-plated • Rated : 50V 10A • Length : 15.30.45.60cm 	<p>KLG-0.5-2</p>  <ul style="list-style-type: none"> • Adapter lead with 0.5mm plug and 2mm plug • Contact surface : Gold-plated • Rated : 50V 10A • Length : 15.30.45.60cm 	<p>KLG-2-4</p>  <ul style="list-style-type: none"> • Adapter lead with 2mm plug and 4mm plug • Contact surface : Gold-plated • Rated : 50V 10A • Length : 25.50.75.100cm
<p>Color : Black, Red, Yellow, Blue, White, Green</p>	<p>Color : Black, Red, Yellow, Blue, White, Green</p>	<p>Color : Black, Red, Yellow, Blue, White, Green</p>	<p>Color : Black, Red, Yellow, Blue, White, Green</p>
<p>CT-26</p>  <ul style="list-style-type: none"> • Ready assembled leads wire approx. 0.6M of 133/0.07mm extra flexible cable • Terminated at one end by a 2mm stackable plug and a 35mm long crocodile clip at the other • Contact surface : Gold-plated 	<p>CT-41</p>  <ul style="list-style-type: none"> • Ready assembled leads wire approx. 1M of 301/0.07mm extra flexible cable • Terminated at one end by a 4mm stackable plug and a 35mm long crocodile clip at the other • Contact surface : Nickel-plated 	<p>CT-42</p>  <ul style="list-style-type: none"> • Ready assembled leads wire approx. 1M of 301/0.07mm extra flexible cable • Terminated at one end by a 4mm stackable safety plug and a 35mm long crocodile clip at the other • Contact surface : Nickel-plated 	<p>LF-51</p>  <ul style="list-style-type: none"> • Fully insulated leads with shrouded BNC plugs complete with moulded-on strain reliefs using RG-58 cable • Black PVC : shield. 50Ω impedance • Length : Overall length approx.1M
<p>Color : Black, Red</p>	<p>Color : Black, Red</p>	<p>Color : Black, Red</p>	<p>Color : Black</p>

<p>LF-56</p>  <ul style="list-style-type: none"> Fully insulated BNC test leads whose impedance 50Ω. With RG-58 cable is moulded to be 35mm long crocodile clips in red and black. Length : Overall length approx.1M. 	<p>LF-61</p>  <ul style="list-style-type: none"> Fully insulated BNC test leads whose impedance 50Ω. With RG-58 cable is moulded to be stackable 4mm plugs in red and black. Length : Overall length approx.1M. 	<p>LF-101</p>  <ul style="list-style-type: none"> The oscilloscope probe body with integral x1 / x10 slide switch which reveals the trimming adjuster when in the x10 position. Bandwidth : DC to 60MHz ± 3db Max. Voltage : 600V DC. Length : Overall length approx.1.2M. 	<p>LF-210</p>  <ul style="list-style-type: none"> The oscilloscope probe body with integral x1 / x10 slide switch which reveals the trimming adjuster when in the x 10 position. Bandwidth : DC to 100MHz ± 3db Max. voltage : 600V DC. Length : Overall length approx.1.2M.
<p>Color : Black</p>	<p>Color : Black</p>	<p>Color : Black</p>	<p>Color : Black</p>
<p>CC-35</p>  <ul style="list-style-type: none"> A set of crocodile clips with insulating vinyl cover Clips are 31mm long. Overall length with sleeve 38mm 	<p>CL-15</p>  <ul style="list-style-type: none"> A set of ten leads wire approx. 370mm long. Terminated at each end with a vinyl insulated crocodile clip 	<p>PC-40</p>  <ul style="list-style-type: none"> A miniature plunger action probes suited for making contact with components on high density PCBs. Overall length 40mm 	<p>PL-15</p>  <ul style="list-style-type: none"> A set of five leads wire approx. 370mm long. Terminated at each end with an insulated miniature probes
<p>Color : Red, Black, Yellow, Green, White</p>	<p>Color : Red, Black, Yellow, Green, White</p>	<p>Color : Red, Black, Yellow, Green, Blue</p>	<p>Color : Red, Black, Yellow, Green, Blue</p>
<p>PT-22</p>  <ul style="list-style-type: none"> A pair of multimeter test leads to suit meter with shrouded 4mm connector. The leads are CE approved. IEC-1010 compatible. Terminated at one end with a rigid probe and a fixed sheath or right angle with retractable shrouded 4mm plug at the other. Length : Overall length approx.1M. Rate : 1000V,10A 	<p>PT-23</p>  <ul style="list-style-type: none"> A set of fully insulated leads with probes and clips. Terminated at one end with a rigid probe including a crocodile clip and a fixed sheath or right angle with retractable shrouded 4mm plug at the other. Length : Overall length approx.1M. Rate : 1000V,10A (clip excepted). 	<p>PT-24</p>  <ul style="list-style-type: none"> A set of fully insulated leads with probes and clips. Terminated at one end with a rigid probe including a crocodile clip and a fixed sheath or right angle with retractable shrouded 4mm plug at the other. Length : Overall length approx.1M. Rate : 1000V,10A (clip excepted). 	
<p>Color : Black, Red</p>	<p>Color : Black, Red</p>	<p>Color : Black, Red</p>	

<p>KSG-30A</p>  <p>KSG-50A</p>  <ul style="list-style-type: none"> • A range of 2/4mm socket designed for easy and quick assembly • Mounting hole 4.2/6.2mm • Contact surface : Gold-plated • Rated : 50V 10/19A 	<p>KSN-34</p>  <p>KSN-56</p>  <ul style="list-style-type: none"> • Uninsulated 2/4mm chassis mounting socket • Mounting hole 4.1/6.1mm • Contact surface : Nickel-plated • Rated : 50V 10/19A
<p>KSG-2</p>  <p>KSG-4</p>  <ul style="list-style-type: none"> • 2/4 mm PCB mounting socket • Mounting hole 2.8/4.8mm • Contact surface : Gold-plated • Rated : 50V 10/19A 	<p>KRN-41</p>  <p>KRN-42</p>  <ul style="list-style-type: none"> • A 4 mm Multilam plug with center hex-shape and threaded post or solder hole • Contact surface : Nickel-plated • Rated : 50V 19A
	

*Remarks : All of our plugs, adaptors and test leads could be sold per pack with hanging card. Please refer to our price list for detail description. Thanks!

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

ORDERING INFORMATION

