



PVC INSULATED MALE DISCONNECTORS

Feature:

1. MAXIMUM ELECTRICAL RATING: 300 VOLTS
2. MAXIMUM TEMPERATURE: 75 °C
3. TERMINAL MATERIAL: BRASS
4. PLATING: ELECTRO TIN PLATED
5. INSULATION MATERIAL: VINYL (PVC)

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-54151736
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Specification:

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

WIRE RANGE AWG / mm ²	ITEM NO.	DIMENSIONS inch (mm)						
		NEMA TAB	B	F	L	E	D	d1
22~16 AWG 0.5~1.5 mm ²	M1-2.8V/5	.020*.110 (0.5*2.8)	.110 (2.8)	.276 (7.0)	.756 (19.2)	.394 (10.0)	.157 (4.0)	.067 (1.7)
	M1-2.8V/8	.032*.110 (0.8*2.8)		.307 (7.8)	.807 (20.5)			
	M1-4.8V/5	.020*.187 (0.5*4.8)	.187 (4.8)	.276 (7.0)	.756 (19.2)			
	M1-4.8V/8	.032*.187 (0.8*4.8)		.307 (7.8)	.807 (20.5)			
	M1-6.4V	.032*.250 (0.8*6.4)	.250 (6.4)	.307 (7.8)	.835 (21.2)			
16~14 AWG 1.5~2.5 mm ²	M2-2.8V/5	.020*.110 (0.5*2.8)	.110 (2.8)	.276 (7.0)	.756 (19.2)	.394 (10.0)	.177 (4.5)	.091 (2.3)
	M2-2.8V/8	.032*.110 (0.8*2.8)		.307 (7.8)	.807 (20.5)			
	M2-4.8V/5	.020*.187 (0.5*4.8)	.187 (4.8)	.276 (7.0)	.756 (19.2)			
	M2-4.8V/8	.032*.187 (0.8*4.8)		.307 (7.8)	.807 (20.5)			
	M2-6.4V	.032*.250 (0.8*6.4)	.250 (6.4)		.835 (21.2)			
12~10 AWG 4~6 mm ²	M5-6.4V	.032*.250 (0.8*6.4)	.250 (6.4)	.307 (7.8)	.913 (23.2)	.512 (12.5)	.217 (5.5)	.134 (3.4)