




Carrier Double- and Triple-Deck Terminal Blocks for Fuse Plugs 2.5 mm² 280 Series

0.08 - 2.5 mm ² 400 V/6 kV/3 ① ② I _N 10 A Terminal block width 5 mm / 0.197 in 8 - 9 mm / 0.33 in ③	AWG 28 - 12 * 300 V, 15 A ④ 300 V, 20 A ⑤	0.08 - 2.5 mm ² 400 V/6 kV/3 ① ② I _N 10 A Terminal block width 5 mm / 0.197 in 8 - 9 mm / 0.33 in ③	AWG 28 - 12 * 300 V, 15 A ④ 300 V, 20 A ⑤	0.08 - 2.5 mm ² 400 V/6 kV/3 ① ② I _N 10 A Terminal block width 5 mm / 0.197 in 8 - 9 mm / 0.33 in ③	AWG 28 - 12 * 300 V, 15 A ④ 300 V, 20 A ⑤
---	---	---	---	---	---



Item No.	Pack. Unit	Item No.	Pack. Unit	Item No.	Pack. Unit
Through/carrier terminal block for pluggable fuse modules		Through/carrier terminal block for pluggable fuse modules with horizontal jumpering on lower level		Through/carrier terminal block for pluggable fuse modules	
blue/gray	280-531 50	blue/gray	280-532 50	gray/gray	280-528 50
gray/gray	280-514 50	gray/gray	280-891 50		
Item-Specific Accessories		Item-Specific Accessories		Item-Specific Accessories	
End and intermediate plate, 2.5 mm thick		End and intermediate plate, 2.5 mm thick		End and intermediate plate, 2.5 mm thick	
orange	280-341 100 (4x25)	orange	280-343 100 (4x25)	orange	280-341 100 (4x25)
gray	280-340 100 (4x25)	gray	280-342 100 (4x25)	gray	280-340 100 (4x25)
Intermediate plate, 1.1 mm thick		Intermediate plate, 1.1 mm thick		Intermediate plate, 1.1 mm thick	
orange	280-366 100 (4x25)	orange	280-369 100 (4x25)	orange	280-366 100 (4x25)
		Adjacent jumper, insulated, I_N = I_N terminal block			
		gray	280-402 200 (8x25)		
		Alternate jumper, insulated, I_N = I_N terminal block			
		gray	280-409 100 (4x25)		

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Accessories		
Appropriate marking systems (see Section 13)		
Insulation stop, ④ 5 pcs/strip, 0.08 - 0.2 mm ² "s" (0.14 mm ² "f-st") white 280-470 200 (8x25)	Fuse plug with pull-tab, AC/DC 24 V, with LED indicator, 6 mm wide 281-512/281-501 50	Operating tool, insulated 10-way 280-440 1
Insulation stop, ④ 5 pcs/strip, 0.25 - 0.5 mm ² light gray 280-471 200 (8x25)	Comb-style jumper bar, insulated, ④ I _N = I _N terminal block 2-way 280-482 200 (8x25) 3-way 280-483 200 (8x25)	WSB Quick marking system, 10 strips with 10 markers per card, WSB Markers 4 mm wide plain 209-701 5
Insulation stop, ④ 5 pcs/strip, 0.75 - 1 mm ² dark gray 280-472 200 (8x25)	Comb-style jumper bar, insulated, I _N = I _N terminal block 10-way 280-490 50 (2x25)	WSB Quick marking system, for fuse plug 281-5.., WSB Markers 4 mm wide F1, ..., F10 (10x) 209-787 5 F11, ..., F20 (10x) 209-700/209-124 F21, ..., F30 (10x) 209-700/209-125 F31, ..., F40 (10x) 209-700/209-126 F41, ..., F50 (10x) 209-700/209-127 5
Fuse plug with pull-tab, 6 mm wide 281-511 50	Alternate comb-style jumper bar, insulated, I _N = I _N terminal block 2-way 280-492 200 (8x25)	
Fuse plug with pull-tab, 6 mm wide 281-512 50	Operating tool, insulated 2-way 280-432 1 3-way 280-433 1	

For list of approvals and user guide, see pages 540 and 542.