

PCE

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

Best. Nr.	Best. Nr.	Best. Nr.	Best. Nr.	Best. Nr.
<b>110V~</b> 50/60Hz 4h	<b>230V~</b> 50/60Hz 3p=6h 4p+5p=9h	<b>400V~</b> 50/60Hz 3p=9h 4p+5p=6h	<b>500V~</b> 50/60Hz 7h	<b>&gt;50-500V~</b> 100-300Hz 10h

### Anbausteckdose

- schräg
- Flansch = 85x70mm  
(16A 3p+4p), 97x80mm
- Lochabstand: 65x50mm  
(16A 3p+4p), 60x97mm
- weitere Flanschgrößen auf Anfrage



IP44

Ampere	Pole	110V~	230V~	400V~	500V~	>50-500V~
16	3	413-4	<b>413-6</b>	413-9	413-7	413-10
16	4	414-4	414-9	<b>414-6</b>	414-7	414-10
16	5	415-4	415-9	<b>415-6</b>	415-7	415-10
32	3	423-4	<b>423-6</b>	423-9	423-7	423-10
32	4	424-4	424-9	<b>424-6</b>	424-7	424-10
32	5	425-4	425-9	<b>425-6</b>	425-7	425-10

### „Turbo Twist“ Anbausteckdose

- schräg
- schraublose Anschluss-technik
- Flansch = 85x70mm  
(16A 3p+4p), 97x80mm
- Lochabstand: 65x50mm  
(16A 3p+4p), 60x97mm
- weitere Flanschgrößen auf Anfrage



IP44

Ampere	Pole	110V~	230V~	400V~	500V~	>50-500V~
16	3	413-4TT	<b>413-6TT</b>	413-9TT	413-7TT	413-10TT
16	4	414-4TT	414-9TT	<b>414-6TT</b>	414-7TT	414-10TT
16	5	415-4TT	415-9TT	<b>415-6TT</b>	415-7TT	415-10TT
32	3	423-4TT	<b>423-6TT</b>	423-9TT	423-7TT	423-10TT
32	4	424-4TT	424-9TT	<b>424-6TT</b>	424-7TT	424-10TT
32	5	425-4TT	425-9TT	<b>425-6TT</b>	425-7TT	425-10TT

### Anbausteckdose

- schräg
- Flansch = 85x70mm (16A 3p+4p), 97x80mm
- Lochabstand: 65x50mm  
(16A 3p+4p), 60x97mm
- für „Turbo Twist“ Ausführung (schraublose Anschluss-technik) fügen Sie bitte „TT“ an, z.B.: 4132-6f78TT
- weitere Flanschgrößen auf Anfrage



IP67

Ampere	Pole	110V~	230V~	400V~	500V~	>50-500V~
16	3	4132-4f78	<b>4132-6f78</b>	4132-9f78	4132-7f78	4132-10f78
16	4	4142-4f78	4142-9f78	<b>4142-6f78</b>	4142-7f78	4142-10f78
16	5	4152-4f78	4152-9f78	<b>4152-6f78</b>	4152-7f78	4152-10f78
32	3	4232-4f78	<b>4232-6f78</b>	4232-9f78	4232-7f78	4232-10f78
32	4	4242-4f78	4242-9f78	<b>4242-6f78</b>	4242-7f78	4242-10f78
32	5	4252-4f78	4252-9f78	<b>4252-6f78</b>	4252-7f78	4252-10f78

### „Power Twist“ Anbausteckdose

- schräg
- mit Lamellenkontakt
- für Ausführung mit Pilotkontakt  
fügen Sie eine „5“ ein, z.B. 4335-6
- weitere Flanschgrößen auf Anfrage



IP66/67

Ampere	Pole	110V~	230V~	400V~	500V~	>50-500V~
63	3	Flansch: 112x100, Lochabst.: 88x80				
63	4	433-4	<b>433-6</b>	433-9	433-7	433-10
63	5	434-4	434-9	<b>434-6</b>	434-7	434-10
		435-4	435-9	<b>435-6</b>	435-7	435-10
		Flansch: 130x120, Lochabst.: 108x100				
125	3	443-4	<b>443-6</b>	443-9	443-7	443-10
125	4	444-4	444-9	<b>444-6</b>	444-7	444-10
125	5	445-4	445-9	<b>445-6</b>	445-7	445-10