



SPECIFICATION:

CONTACT RATING: 6A 250VAC, 10A 125VAC

INSULATION RESISTANCE: 500V d.c. for 1 min.

ELECTRIC STRENGTH: 2000V a.c. for 1 min.

NO	DESCRIPTION	MATERIAL	QTY	SGS REPORT NO.
1	PIN	C3604 ALLOY COPPER, NICKEL	2	CE/2005/B2486
2	HOUSING	ABS 777B, BLACK	1	CE/2005/31101
3	GROUND	ABS 777B, BLACK	1	CE/2005/31101
4	CONTACT	BRONZE, NICKEL	2	CE/2006/65586

Cd < 100ppm
 Cr+6 < 1000ppm
 Hg < 1000ppm
 Pb < 1,000ppm
 銅合金 Pb < 40,000ppm
 PBB < 1000ppm
 PBDE < 1000ppm

TOLERANCES
0.5MM-5MM=±0.2MM
5MM-30MM=±0.4MM
30MM-120MM=±0.6MM
120MM-315MM=±1.0MM
315MM-1000MM=±1.6MM
1000MM-2000MM=±2.4MM

修正日期	修正說明	核准日期 Date	設計 Designed By	比例尺 Scale
95.7.28	UPDATE SGS報告	28 JUL 2006	C.J HUANG	1:1
94.2.22	增加規格說明	核准 Approved By	繪圖 Drew By	單位 UNIT
		J.F. WANG	C.T WANG	m/m

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

WTN-01-1152B/4MM	REF. NO.
EUROPE TYPE	
ADAPTOR PLUG, 6A 250V AC	