




# Cat.5e RJ-45 Keystone Jack (UTP) / Dual Type (Krone & 110)



### Color coding information

T568B:	T568A:
1—WH/OR	1—WH/GN
2—OR	2—GN
3—WH/GN	3—WH/OR
4—BL	4—BL
5—WH/BL	5—WH/BL
6—GN	6—OR
7—WH/BR	7—WH/BR
8—BR	8—BR

Dimensions : m/m



### Performance:

Meets Cat.5e EIA/TIA 568B.1 Standard.

### Materials:

Plastic Body : Fireproof ABS UL-94V0  
 RJ-45 Jack : 8P8C 50 micro inches gold plated  
 PCB : FR-4 / 1.0mm  
 IDC Body : Fireproof ABS UL-94V0  
 IDC Pin : Bronze & Tinned

Label Color Code: T568 A/B

IDC Description: For 22-26 AWG.  
 For 110 or Krone punch-down Tool

### Electrical Specifications:

Insulation Resistance : 500M ohms (min.)  
 Contact Resistance : 20m ohms (max.)  
 Current Rating : 1.5 Amps  
 DC Resistance : 0.1 ohm (max.)  
 Withstanding Voltage : 1000 VAC RMS @ 60Hz / 1 min.

### Mechanical Specifications:

IDC Punch Down Cycle : Over 25 Cycles (min.)  
 RJ-45 Jack Insertion Cycle : Over 1000 Cycles (min.)

Operation Temperature : -40 ~ +70 degree / C

DRAWING:		ITEM NO:	9037
	APPR	CUSTOMER:	
SMT:	CHECK	DATE:	
SCALE:	DESIGN	TOLERANCE:	± 1 X ± 0.2 - XX ± 0.15

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)