


Num	Category	Describe
1	Max Current	0.8A
2	Cable gauge (AWG)	14-26 AWG
3	IDC Pitch:	Pitch:2.54mm
4	PCB Material	FR4
5	IDC Withstanding voltage	300V AC/MINUTE
6	IDC Operating temperature	-20℃ to 105℃
7	Rated voltage according to	UL:E31899
8	Rated current according to	UL:E31899
9	IDC Material:	INSULATOR:PBT 30%GF; CONTACT:COPPER ALLOY
10	Box size w/label	L130*W95*H54mm /
11	Packing	



制作	Hero.Xu	日期	2021.02.22				名称	端子台		型号	IDC40P-CK (卡线式)																			
审核							版本	Ver:1.0		客户编号																				
核准																														
未注线性公差GB1804-m(单位:mm) <table border="1"> <thead> <tr> <th>尺寸</th> <th>s3</th> <th>3-6</th> <th>6-30</th> <th>30-120</th> <th>120-400</th> <th>400-1000</th> <th>1000-2000</th> <th>2000-4000</th> </tr> </thead> <tbody> <tr> <td>公差</td> <td>0.1</td> <td>0.15</td> <td>0.2</td> <td>0.3</td> <td>0.5</td> <td>0.8</td> <td>1.2</td> <td>2.0</td> </tr> </tbody> </table> 角度公差 ± 0.5°													尺寸	s3	3-6	6-30	30-120	120-400	400-1000	1000-2000	2000-4000	公差	0.1	0.15	0.2	0.3	0.5	0.8	1.2	2.0
尺寸	s3	3-6	6-30	30-120	120-400	400-1000	1000-2000	2000-4000																						
公差	0.1	0.15	0.2	0.3	0.5	0.8	1.2	2.0																						
							投影角度	图纸比例	第 1 张 共 1 张																					
								1:1	中山市肯博电子科技有限公司 www.kingpow.cn																					