

SIPLUS NET PB CONNECTOR FOR -
25 ... +60 DGR C AND MED BASED
ON 6GK1500-0EA02



勝特力材料 886-3-5753170
 胜特力电子(上海) 86-21-34970699
 胜特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

[nicht versorgt: PMD_ABS675_001_000]

•	9.6 kbit/s...12 Mbit/s
Interfaces	
Number of electrical connections	2
• [not supplied - for network components and terminal equipment]	1
Design of the electrical connection / [nicht versorgt - FastConnect]	No
Mechanical data	
material / of the housing	metal
Design, dimensions and weight	
Width	15 mm
Height	57 mm
Depth	39 mm
Net weight	100 g
Permitted ambient conditions	
Ambient temperature	
• during operating phase	-25 °C...60 °C
• during storage	-25 °C...80 °C
• during transport	-25 °C...80 °C
Relative humidity / at 25 °C / without condensation / during the operating phase / maximum	100 %
Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [nicht versorgt - silikonfrei]	Yes
Composant produit	
• [nicht versorgt - PG-Anschlussbuchse]	No
• décharge de traction	Yes
Standards, specifications, approvals	
Verification of suitability	

- RoHS conformity
- UL-registration

Yes
No

6AG1500-0EA02-2AA0 SIPLUS NET PB BUSANSCHLUSS

SIPLUS NET PB CONNECTOR FOR -
25 ... +60 DGR C AND MED BASED
ON 6GK1500-0EA02



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Interfaces

Number of electrical connections

- 2
- [nicht versorgt - für Netzkomponenten und Endgeräte] 1

电气连接设计 / [nicht versorgt - FastConnect] 否

Mechanical data

材料 / 外壳的

金属

Design, dimensions and weight

- 宽度 15 mm
- 高度 57 mm
- 深度 39 mm
- 净重 100 g

Permitted ambient conditions

环境温度

- 在运行阶段 -25 °C...60 °C
- 在储存期间 -25 °C...80 °C
- 在运输期间 -25 °C...80 °C

相对的空气湿度 / 在25 °C时 / 无冷凝 / 在运行阶段 / 最大的 100 %

Product properties, functions, components / general

Product feature / [nicht versorgt - silikonfrei] 是

产品构件

- [nicht versorgt - PG-Anschlussbuchse] 否
- 应变释放装置 是

Standards, specifications, approvals

[nicht versorgt: PMD_ABS586_001_000]

- 是
- UL许可证 否