

## TRP-C41 Ethernet to fiber media converter



勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-54151736  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

### Introduction

TRP-C41 is a device for Ethernet extension over fiber, it supports point-to-point and networked systems. The high fiber bandwidth connections solve problems with electrical noise and different ground potentials over long transmission lines. TRP-C41 supports 10/100Base-TX transmissions up to 100 meters and 100Base-FX transmissions up to 20KM . It is the perfect solution for wide distance connections with high immunity to electrical noise.

### Features

- Wide input range DC power supply.
- Plug-and-Play design for the installation within seconds.
- Compact and Rugged Metal case capable of withstanding harsh environment.
- Data rate: 10/100Mbps auto-negotiation and half-/Full-duplex mode on TX port.
- Auto MDI-X/MDI-II for 10/100Base-TX port.
- Provides media conversion from UTP to Fiber Optic media types
- Supports link fault pass through function.
- Supports far end fault function.
- LED display to indicate the whole working status.
- 3 power input types: Direct USB power, external DC adapter and screw terminal.
- Support IEEE Standard: 802.3u 100BaseTX & 100BaseFX.

### Specifications

- Cable: Fiber cable (9/125um).
- One 10/100Base-TX auto-negotiation Ethernet RJ-45 port.
- One 100Mbps fiber port with Single-mode SC connector.
- Built in 128Kb RAM for data buffer.
- Wavelength: 1310 nM.
- Fiber Power:-15 ~ -8 dBm.
- LED indicator: Power and power and TX and fiber link/activity, full/half, 10/100MB.
- Distance : 20KM can be up to 60KM (option).
- Speed : Auto 10/100MB.
- Power Consumption: 12V/160mA.
- Power requirement: USB port power or DC input or screw terminal from +10 to 30V.
- Operating temperature: -10 to 50°C .
- Storage temperature : -20 to 70°C .
- Humidity: 10-90% Non-condensing.
- Dimension: 151mm X 75mm X 26mm .
- Weight: 400g .

## Accessories

TRP-C41H

Distance : 40KM

Wavelength: 1490 nM



PWR-AD12V-Auto (Option)

Switching Adaptor

Input:100~240VAC 50/60Hz 260mA

Output: DC 12V/1A

Certificate: CE, FCC, UL, PSE



[T-snap](#) (Option)

DIN rail mounting adapter



勝特力材料 886-3-5753170

勝特力电子(上海) 86-21-54151736

勝特力电子(深圳) 86-755-83298787

[Http://www.100y.com.tw](http://www.100y.com.tw)